



 6961 PEACHTREE INDUSTRIAL
 BLVD, SUITE 200 NORCROSS,
 GEORGIA 30092
 PH: 678-895-6094
 www.hammondeingeneers.com


ELECTRICAL LEGENDS	
SYMBOL	DESCRIPTION
○	DUPLEX RECEPTACLE - WALL MOUNTED
○	SINGLE RECEPTACLE - WALL MOUNTED
□	SINGLE "GFCI" RECEPTACLE - WALL MOUNTED
□	DUPLEX RECEPTACLE - CEILING MOUNTED
□	DUPLEX RECEPTACLE - WALL MOUNTED - COUNTER HEIGHT
□	SWITCHED OUTLET
□	USB TYPE COMBO OUTLET - WALL MOUNTED
□	QUAD RECEPTACLE - WALL MOUNTED
□	DUPLEX "GFCI" RECEPTACLE - WALL MOUNTED
□	DUPLEX "GFCI" RECEPTACLE - WALL MOUNTED - COUNTER HEIGHT
□	DUPLEX "GFCI" RECEPTACLE - WALL MOUNTED
□	SPECIAL OUTLET - WALL MOUNTED
□	DUPLEX RECEPTACLE - IN FLUSH FLOOR BOX
○	JUNCTION BOX
○	JUNCTION BOX - WALL MOUNTED
○	WALL SWITCH - SINGLE POLE - SINGLE THROW
○ ³	WALL SWITCH - 3 WAY - SINGLE POLE - SINGLE THROW
○ ⁴	WALL SWITCH - 4 WAY - SINGLE POLE - SINGLE THROW
○ ⁵	WALL OCCUPANCY SENSOR - MOTION & INFRARED
○ ⁶	WALL MOUNTED KEYED SWITCH
○ ⁷	WALL MOUNTED ZONED SWITCH
○ ⁸	OCCUPANCY SENSOR - CEILING MOUNTED
D	DIMMER SWITCH - WALL MOUNTED
D _{OS}	DIMMER SWITCH - WALL OCCUPANCY SENSOR - MOTION & INFRARED
D ₃	DIMMER SWITCH - 3 WAY - WALL MOUNTED
TC	TIME CLOCK

CODE COMPLIANCE	
THESE PLANS WERE PREPARED AND SHALL COMPLY WITH THE BUILDING	
INTERNATIONAL BUILDING CODE, 2018 EDITION, WITH GEORGIA AMENDMENTS (2020), (2022)	
INTERNATIONAL ENERGY CONSERVATION CODE, 2015 EDITION	
INTERNATIONAL FIRE CODE, 2018 EDITION	
NATIONAL ELECTRICAL CODE, 2023 EDITION, WITH GEORGIA AMENDMENTS (2021)	


ABBREVIATIONS	
ACT	ABOVE COUNTERTOP OR BACKSPLASH
AC	ALTERNATING CURRENT
AL	ALUMINUM
AMP	AMPERES
AMP/AFG	AMPERE-FUSED FLOOR/GRADE
AHU	AIR HANDLING UNIT
APPROX	APPROXIMATELY
ARCH	ARCHITECTURAL
AWG	AMERICAN WIRE GAUGE
BOARD	BOARD
BLDG	BUILDING
CABIN	CABINET
CAPACITY	CAPACITY
CATV	CABLE TELEVISION
CBB	CABLE TELEVISION BACKBOARD
CKT	CIRCUIT
CEILING	CEILING
CIR	CIRCUIT BREAKER
CL	CENTER LINE
COL	COLUMN
COM	COMMIT
CONN	CONNECTION
CONT	CONTINUATION
C&P	CORD AND PLUG
CPT	CONTROL POWER TRANSFORMER
CT	CURRENT TRANSFORMER
CU	COPPER
DET	DETAIL
DF/EDF	ELECTRICAL DRINKING FOUNTAIN
DOWN	DOWN
DS	DISCONNECT SWITCH
DWV	DRAWING
EA	EACH
EEC	ELECTRICAL CONTRACTOR
EF	EXHAUST FAN
ELEC	ELECTRIC
EQ	EQUIPMENT
EXTIN	EXTIN
FA	FIRE ALARM
FSD	FLAME SMOKE DAMPER
MAIN	MAIN
MLO	MAIN LUG ONLY
MOPC	MAIN OVERCURRENT PROTECTION
MOD	MOTOR OPERATED DAMPER
MRS	MOTOR RATE SWITCH
NEC	NATIONAL ELECTRICAL CODE
NES	NASHVILLE ELECTRIC SERVICE
NF	NIGHT
NL	NIGHT LIGHT
NO.	NUMBER
NTS	NOT TO SCALE
P&V	POLYVINY CHLORIDE CONDUIT
PNL	PANEL
PVC	POLYVINYL CHLORIDE CONDUIT
RTU	ROOF TOP UNIT
SH	SWITCH
SW	SWITCH
TR	TRANSFORMER
TBS	TELEPHONE BACKBOARD
TELE	TELEPHONE
UNO	UNLESS OTHERWISE
WP	WEATHERPROOF

EMERGENCY RESPONDER RADIO COVERAGE	
AS A DEDICATE ALTERNATE, PROVIDE A BOOSTER SYSTEM, PER SPECIFICATION 285000, FOR THE ENTIRE BUILDING TO BOOST THE RADIO COVERAGE/STRENGTH ADEQUATE FOR THE PUBLIC SAFETY COMMUNICATIONS SYSTEMS OF THE JURISDICTION AT THE EXTERIOR OF THE BUILDING. PROVIDE CONDUIT INFRASTRUCTURE, UNDER BASE BID, DURING CONSTRUCTION SUCH THAT NO CONDUIT WILL HAVE TO BE ADDED AT TIME OF PROJECT BID. DURING CONSTRUCTION SUCH THAT NO CONDUIT WILL HAVE TO BE ADDED AT TIME OF SHEET ROCKING, PER SPECIFICATION SECTION 285300.	

SHEET INDEX - ELECTRICAL	
NUMBER	NAME
E0.01	ELECTRICAL COVER SHEET
E1.01	ELECTRICAL SITE PLAN
E1.11	ELECTRICAL POWER PLAN - LEVEL 1
E1.12	ELECTRICAL POWER PLAN - LEVEL 2
E1.13	ELECTRICAL LIGHTING PLAN - LEVEL 1
E2.01	ELECTRICAL PANEL SCHEDULES
E9.01	ELECTRICAL - SINGLE LINE DIAGRAM


LIGHTING FIXTURE SCHEDULE			
Type Mark	Description	Wattage	Manufacturer
A1	2x4 RECESSED TROFFER	80 W	TBD
A1E	2x4 RECESSED TROFFER W/ BATTERY BACKUP	80 W	TBD
B2	2x2 RECESSED TROFFER	36 W	METALUX
B2E	2x2 RECESSED TROFFER W/ BATTERY BACKUP	36 W	METALUX
D6	6" LED DOWNLIGHT	15 W	HALO
D6E	6" LED DOWNLIGHT W/ BATTERY BACKUP	15 W	HALO
EM	EMERGENCY BATTERY BACKUP	10 W	TBD
L1	FOCUS W/ BULB LED	67 W	FOCAL POINT
L8	6x1 LINEAR RECESSED LED	41 W	METALUX
L8E	6x4 LINEAR RECESSED LED W/ BATTERY BACKUP	41 W	METALUX
L11	4" INDUSTRIAL LED STRIP	40 W	METALUX
L11E	4" INDUSTRIAL LED STRIP W/ BATTERY BACKUP	40 W	METALUX
P1	6x4 GLOW RING PENDANT	175 W	OCL
P2	8x4 GLOW RING PENDANT	205 W	OCL
X	LED DOUBLE FACE EXIT GREEN LETTERING	5 W	LITHONIA
X1	LED EXIT SIGN / EMERGENCY LIGHT COMBO	10 W	TBD

ELECTRICAL GENERAL NOTES	
1.	ALL WORK THIS DIVISION SHALL COMPLY WITH ALL BUILDING CODES, LAWS, REGULATIONS, ORDINANCES, AND THE REQUIREMENTS OF 2014 NATIONAL ELECTRICAL CODE.
2.	THE CONTRACTOR SHALL KEEP A RECORD OF THE CHANGES WHICH ARE IN CONFLICT WITH THESE DRAWINGS AND SPECIFICATIONS AT THE CONSTRUCTION SITE. THE OWNER SHALL SUBMIT AS BUILT PRINTS TO THE OWNER.
3.	ALL SYSTEMS, EQUIPMENT, COMPONENTS, WORK, ETC. PROVIDED UNDER THIS DIVISION SHALL BE COVERED BY A MINIMUM ONE YEAR GUARANTEE STARTING AT THE TIME OF FINAL ACCEPTANCE OF THE WORK BY THE OWNER. ANY DEFECTS IN THE WORK SYSTEMS, EQUIPMENT, OR COMPONENTS FOUND DURING THIS YEAR SHALL BE CORRECTED AT NO CHARGE. THE GUARANTEE SHALL INCLUDE PROVIDING ALL LABOR AND MATERIALS FOR REPAIRS.
4.	ALL BRANCH CIRCUIT CONDUCTORS SHALL BE COPPER WITH TYPE THW OR THAN INSULATION AND THE MINIMUM WIRE SIZE SHALL BE #14 AWG. FOR 15A FOR 15A WHERE USED IN RESIDENTIAL/ULVING UNITS AND #12 AWG FOR 20A CIRCUITS UNLESS NOTED OTHERWISE, OR NOT ALLOWED BY LOCAL JURISDICTION HAVING AUTHORITY.
5.	ALL WORK MUST BE PERFORMED IN A NEAT AND WORKMANLIKE MANNER ACCORDING TO GENERALLY ACCEPTED PRINCIPALS OF FIRST CLASS WORKMANSHIP.
6.	ALL PENETRATIONS THRU RATED WALLS, FLOORS AND CEILINGS SHALL BE FIRE STOPPED PER NEC 300.21. ALSO SEE SHEET E02. FIRE STOPPING SHALL MATCH UL RATING OF WALL, FLOOR, OR CEILING PENETRATED.
7.	ALL CIRCUITS SHALL BE MATCHED IN SIZE, LENGTH, AND AMPERAGE. EQUIPMENT, OUTLETS, AND SWITCHES WHICH ARE SHOWN TO BE OF THE SAME SIZE AND CAPACITY SHALL BE PLACED IN THE SAME GENERAL AREA.
8.	COORDINATE RECEPTACLE NEMA TYPE AND VOLTAGE WITH EQUIPMENT.
9.	ALL OUTLETS AND SWITCHES ARE TO BE FLUSH MOUNTED UNLESS NOTED OTHERWISE.
10.	LABELED EQUIPMENT, OUTLETS, AND SWITCHES SHALL BE PLACED IN THE SAME GENERAL AREA AS THE EQUIPMENT, OUTLET, OR SWITCH THEY ARE CONNECTED TO AT THE TIME OF INSTALLATION.
11.	VERIFY LOCATION OF ALL MOTORS AND EQUIPMENT BEFORE ROUGH-IN.
12.	ALL CONDUITS CROSSING EXPANSION JOINTS SHALL HAVE EXPANSION TYPE FITTINGS. WIRING SHALL BE INSTALLED AT DEPTHS BELOW FINISHED GRADE (BELLOWS SLAB AND SUB-BASE LEVEL) AS PER NEC ARTICLE 300.50.
13.	MINIMUM CONDUIT SIZE SHALL BE:
A.	ABOVE GRADE: 3/4"
B.	BELOW GRADE: 3/4"
14.	COMMON CONDUIT MAY BE USED AS PER NEC FOR MULTIWIRE BRANCH CIRCUITS. SEPARATE NEUTRAL SHALL BE PROVIDED FOR ALL CIRCUITS CONNECTED TO GROUND FAULT CIRCUIT INTERRUPTER TYPE DEVICES, UNLESS OTHERWISE NOTED. SEPARATE NEUTRAL SHALL BE PROVIDED FOR ALL ARC FAULT WALLS, FLOOR, AND CEILINGS.
15.	ALL BRANCH CIRCUITS SHALL INCLUDE A GREEN INSULATED GROUND WIRE, SIZED PER NEC TABLE 250.122 OR AS SHOWN CONNECTED TO EACH DEVICE AND OUTLET BOOTH THE CIRCUIT, AND TO THE GROUND BUS. MULTIPLE WIRE BRANCH CIRCUITS WITH COMMON NEUTRAL SHALL BE PROVIDED AS PER NEC. UNLESS OTHERWISE NOTED.
16.	IN CASES WHERE CONFLICTS OCCUR BETWEEN DRAWINGS AND SPECIFICATIONS, OR BETWEEN DIFFERENT TRADES, AS WELL AS CASES OF ANY OMISSION OF INFORMATION, NOTIFY THE ARCHITECT AND PROCURE RESOLUTION OF THE CONFLICT OR OMISSION BEFORE PROCEEDING WITH THE INSTALLATION.
17.	ALL ANGLED/RECESSED BRANCH RECEPTACLES FOR CIRCUITS LONGER THAN 70'-0" SHALL BE MINIMUM #10 AWG. LONGER THAN 150' SHALL BE #8 AWG.
18.	THE DRAWINGS INDICATE THE GENERAL ARRANGEMENT AND LOCATION OF ELECTRICAL WORK. DATA PRESENTED ON THE DRAWINGS ARE AS ACCURATE AS PLANNING CAN DETERMINE, BUT FIELD VERIFICATION OF ALL DIMENSIONS, LOCATIONS, LEVELS, ETC. TO SUIT FIELD CONDITION IS RECOMMENDED. THE CONTRACTOR SHALL COORDINATE WITH OTHER TRADES TO AVOID CONFLICT WITH THE PIPING DUCT WORK.
19.	COORDINATE WITH OTHER TRADES SO THAT INSTALLATION OF ELECTRICAL OUTLETS AND EQUIPMENT WILL BE PROPERLY COORDINATED. CHECK CONDUIT, FIXTURE AND OTHER EQUIPMENT LOCATIONS WITH OTHER TRADES TO AVOID CONFLICT WITH THE PIPING DUCT WORK.
20.	THE GENERAL CONTRACTOR SHALL PROVIDE NOTICE TO THE ARCHITECT/ENGINEER THAT THERE HAS BEEN A FACE-TO-FACE MEETING WITH THE MECHANICAL, PLUMBING, FIRE PROTECTION AND ELECTRICAL SUBCONTRACTORS TO COORDINATE THEIR WORK. THIS MUST BE DONE PRIOR TO ORDERING ANY EQUIPMENT AND SPECIFICATIONS. AFTER THE MEETING, THE CONTRACTOR SHALL PROVIDE A WRITTEN CONFIRMATION OF THE DISCUSSIONS, AFTER WHICH THE CONTRACTOR SHALL PROVIDE NOTICE IN WRITING TO THE A/E THAT THIS HAS BEEN DONE AND THERE ARE NO DISCREPANCIES. FAILURE TO MEET DOES NOT ENTITLE CONTRACTOR TO A CHANGE ORDER FOR INCOMPATIBLE EQUIPMENT AND SERVICE CHARACTERISTICS.
21.	PROVIDE UNSPLICED HOT WIRE TO ALL EMERGENCY/EXIT LIGHTING.
22.	PROVIDE A GND WIRE TO THE GND BUS.
23.	COMBUSTIBLE MATERIALS ARE NOT ALLOWED WITHIN AREAS WHERE PLENUM AIR SYSTEMS ARE BEING USED.
24.	THE CONTRACTOR SHALL PROVIDE AND INSTALL WIRING AND CIRCUIT ALL EQUIPMENT, MOTORS, AND OTHER ITEMS NOT EXPLICITLY SHOWN, BUT INDICATED, IN CONTRACT DOCUMENTS OR IN SPECIFICATIONS. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF SAID ITEMS BETTER THAN THE CONTRACTOR'S TRADES.
25.	NO PIPING, DUCT, OR EQUIPMENT FOREIGN TO THE ELECTRICAL INSTALLATION SHALL BE INSTALLED ABOVE ANY ELECTRICAL PANEL/BOARD, LOAD CENTER, MOTOR CONTROL CENTER, OR SWITCHBOARD. PER NEC ARTICLE 110.26 (i)(3).
26.	THERE SHALL BE NO BACK TO BACK RECEPTACLE PLATE IN USE. PROVIDE MINIMUM HORIZONTAL SPACE BETWEEN OUTLETS AT OPENINGS IN THE WALL.

**GENERAL NOTES:**

(THIS SHEET ONLY)

1. GENERAL ELECTRICAL CONTRACTOR TO COORDINATE THE POWER CONDUITS WITH OTHER ELEMENTS ON SITE.
2. REFERENCE CIVIL DRAWINGS FOR UTILITY TRANSFORMER LOCATION.
3. COORDINATE WITH CIVIL, ARCHITECT, AND OWNER FOR EV CHARGER LOCATIONS IN COORDINATION WITH THE PARKING LOT.
4. SITE LIGHTING WILL BE PROVIDED BY GEORGIA POWER. ELECTRICAL CONTRACTOR TO COORDINATE WITH SITE LIGHTING.
5. TELECOM SERVICE ENTRANCE TO BE COORDINATED BY LOW VOLTAGE CONTRACTOR.



ESTORIA STREET

2 ELECTRICAL POWER SITE
SCALE: 1" = 20'-0"
1" = 20'-0" 20 0 20 40
SCALE FEET

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19



CDH
ARCHITECTURE

3300 Cumberland Blvd. SE
Suite 100
Atlanta, GA 30339
770.423.0016
www.cdhpartners.com

COPYRIGHT © 2023 by CDH PARTNERS INC.
All rights reserved.



6961 PEACHTREE INDUSTRIAL
BLVD, SUITE 208 NORCROSS,
GEORGIA 30092
PH: 678-895-6094
www.hammondengeers.com

COPYRIGHT © 2023 by HAMMOND ENGINEERS INC.
All rights reserved.

GRADY HEALTH SYSTEM
Corner of Memorial Drive & Estoria Street
Atlanta GA 30316

GRADY ESTORIA URGENT CARE

PROJECT NO: 25132.00
DD PACKAGE 12/18/25

NOT ISSUED FOR
CONSTRUCTION


12/18/25

DD PACKAGE
SHEET TITLE
ELECTRICAL
POWER PLAN -
ROOF

SHEET NUMBER


E1.12








PROJECT NO:	25132.00
DD PACKAGE	12/18/25



12/18/25



1 Electrical Riser Diagram

SCALE: NO SCALE

DISTRIBUTION PANELBOARD "HDP" SCHEDULE																																																																																																	
VOLTS: 480/277 Wye		BUS: 1000 A		MOUNTING: SURFACE																																																																																													
PHASES: 3		MAIN: 1000 A		LOCATION: ELECTRICAL ROOM 124																																																																																													
NOTES:																																																																																																	
<table border="1"> <thead> <tr> <th>CKT</th> <th>CIRCUIT DESCRIPTION</th> <th>POLES</th> <th>FRAME</th> <th>TRIP</th> <th>LOAD (kVA)</th> <th>REMARKS</th> </tr> </thead> <tbody> <tr><td>1</td><td>PANEL HM1</td><td>3</td><td>400 A</td><td>300 A</td><td>77.4 kVA</td><td></td></tr> <tr><td>2</td><td>TRANSFORMER L1</td><td>3</td><td>200 A</td><td>125 A</td><td>67.5 kVA</td><td></td></tr> <tr><td>3</td><td>TRANSFORMER LEV</td><td>3</td><td>200 A</td><td>125 A</td><td>39.9 kVA</td><td></td></tr> <tr><td>4</td><td>XRAY ITEM ID: XRYGD-005</td><td>3</td><td>200 A</td><td>125 A</td><td>83.0 kVA</td><td></td></tr> <tr><td>5</td><td>SURGE PROTECTIVE DEVICE</td><td>3</td><td>100 A</td><td>60 A</td><td>0.0 kVA</td><td></td></tr> <tr><td>6</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>7</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>9</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>10</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>11</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>12</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>							CKT	CIRCUIT DESCRIPTION	POLES	FRAME	TRIP	LOAD (kVA)	REMARKS	1	PANEL HM1	3	400 A	300 A	77.4 kVA		2	TRANSFORMER L1	3	200 A	125 A	67.5 kVA		3	TRANSFORMER LEV	3	200 A	125 A	39.9 kVA		4	XRAY ITEM ID: XRYGD-005	3	200 A	125 A	83.0 kVA		5	SURGE PROTECTIVE DEVICE	3	100 A	60 A	0.0 kVA		6							7							8							9							10							11							12						
CKT	CIRCUIT DESCRIPTION	POLES	FRAME	TRIP	LOAD (kVA)	REMARKS																																																																																											
1	PANEL HM1	3	400 A	300 A	77.4 kVA																																																																																												
2	TRANSFORMER L1	3	200 A	125 A	67.5 kVA																																																																																												
3	TRANSFORMER LEV	3	200 A	125 A	39.9 kVA																																																																																												
4	XRAY ITEM ID: XRYGD-005	3	200 A	125 A	83.0 kVA																																																																																												
5	SURGE PROTECTIVE DEVICE	3	100 A	60 A	0.0 kVA																																																																																												
6																																																																																																	
7																																																																																																	
8																																																																																																	
9																																																																																																	
10																																																																																																	
11																																																																																																	
12																																																																																																	
<table border="1"> <thead> <tr> <th>LOAD CLASSIFICATION</th> <th>CONNECTED LOAD</th> <th>DEMAND FACTOR</th> <th>ESTIMATED LOAD</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr><td>Lighting</td><td>4306 VA</td><td>125.00%</td><td>5383 VA</td><td>CONNECTED LOAD: 267845 VA</td><td></td><td></td></tr> <tr><td>Lighting - Dwelling Unit</td><td>40 VA</td><td>125.00%</td><td>50 VA</td><td>CALCULATED LOAD: 252842 VA</td><td></td><td></td></tr> <tr><td>Power</td><td>12452 VA</td><td>100.00%</td><td>12452 VA</td><td></td><td></td><td></td></tr> <tr><td>Receptacle</td><td>55960 VA</td><td>71.25%</td><td>39874 VA</td><td></td><td></td><td></td></tr> <tr><td>X-Ray</td><td>83001 VA</td><td>100.00%</td><td>83001 VA</td><td>CONNECTED AMPERES: 322 A</td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td><td>CALCULATED AMPERES: 304 A</td><td></td><td></td></tr> </tbody> </table>							LOAD CLASSIFICATION	CONNECTED LOAD	DEMAND FACTOR	ESTIMATED LOAD				Lighting	4306 VA	125.00%	5383 VA	CONNECTED LOAD: 267845 VA			Lighting - Dwelling Unit	40 VA	125.00%	50 VA	CALCULATED LOAD: 252842 VA			Power	12452 VA	100.00%	12452 VA				Receptacle	55960 VA	71.25%	39874 VA				X-Ray	83001 VA	100.00%	83001 VA	CONNECTED AMPERES: 322 A							CALCULATED AMPERES: 304 A																																												
LOAD CLASSIFICATION	CONNECTED LOAD	DEMAND FACTOR	ESTIMATED LOAD																																																																																														
Lighting	4306 VA	125.00%	5383 VA	CONNECTED LOAD: 267845 VA																																																																																													
Lighting - Dwelling Unit	40 VA	125.00%	50 VA	CALCULATED LOAD: 252842 VA																																																																																													
Power	12452 VA	100.00%	12452 VA																																																																																														
Receptacle	55960 VA	71.25%	39874 VA																																																																																														
X-Ray	83001 VA	100.00%	83001 VA	CONNECTED AMPERES: 322 A																																																																																													
				CALCULATED AMPERES: 304 A																																																																																													

PROJECT GENERAL NOTES:

1. COORDINATE LOCATION OF EQUIPMENT, JUNCTION BOXES, OUTLETS, CONDUIT, ETC. ACCORDING TO THE PROJECT GENERAL CONDITIONS.
2. HORIZONTAL TELECOMMUNICATIONS/DATA CABLING SHALL BE ROUTED DIRECTLY BETWEEN COMPONENTS WITH NO JUNCTIONS OR SPLICES IN CABLING AND SHALL BE LABELED ACCORDING TO TIA-606A/B STANDARDS AND SPECIFICATIONS.
3. THE DRAWINGS INDICATE ONE ROUTING METHOD OF THE CABLING PATHWAY. CHANGES MAY BE MADE TO THE PATHWAY SYSTEM ROUTING TO ACCOMMODATE SITE CONDITIONS OR TO SIMPLIFY INSTALLATION PROVIDING THAT NOTED CONDUIT SIZE OR LARGER IS MAINTAINED AND DISTANCE LIMITATIONS LISTED BELOW ARE NOT EXCEEDED.
4. FOR HORIZONTAL LOW VOLTAGE CABLING, PROVIDE EMT RACEWAY OR LADDER RACK FROM LOW VOLTAGE BACKBOX TO ACCESSIBLE CEILING SPACE. CONDUIT AND CABLES SHALL BE SUPPORTED AT 3'-0" MAX INTERVALS. J-HOOK PATHWAYS SHALL BE ESTABLISHED TO SUPPORT CABLING AND PREVENT CONTACT OF THE CABLING WITH BUILDING STRUCTURE AND OTHER MECHANICAL SYSTEMS AND MECHANICAL SYSTEMS MOUNTING HARDWARE.
5. ALL CABLING IN SLAB ON GRADE OR BELOW GRADE TO BE OUTSIDE PLANT - WET LOCATION RATED. OSP CABLING TO BE ROUTED IN METAL CONDUIT SYSTEM TO TELECOM ROOM. OSP CABLING NOT PERMITTED TO BE EXPOSED BEYOND 50' FROM THE POINT OF BLDG ENTRY NOR IN PLENUM SPACE.
6. ALL CONDUITS TO BE 1" TRADE SIZE (UNLESS NOTED OTHERWISE).
7. ALL CONDUIT INSTALLATION TO MEET REQUIREMENTS OF NATIONAL ELECTRIC CODE (NEC) CURRENT EDITION.
8. ALL CONDUIT AND BACKBOX INSTALLATION/ROUGH-IN TO BE COMPLETED BY ELECTRICAL CONTRACTOR. ALL CONDUITS TO BE ROUTED FROM BACKBOX TO NEAREST ACCESSIBLE CEILING SPACE OR STRUCTURED CABLING PATHWAYS.
9. CONDUITS SHALL BE REMAILED TO ELIMINATE SHARP EDGES. METALLIC CONDUITS SHALL BE TERMINATED WITH AN INSULATED BUSHING. PULL STRINGS WITH A MINIMUM PULL RATING OF 400 POUNDS SHALL BE PROVIDED.
10. NO CONDUIT RUN SHALL CONTAIN A SINGLE BEND GREATER THAN 90° OR AN AGGREGATE OF BENDS GREATER THAN 180° BETWEEN PULLING POINTS. NO CONDUIT SHALL EXCEED 10 FT BETWEEN PULLING POINTS. PROVIDE JUNCTION BOXES WHERE REQUIRED TO MAINTAIN BEND AND DISTANCE REQUIREMENTS.
11. NO SECTION OF CONDUIT SHALL EXCEED 100 FEET. RUNS IN EXCESS OF 100 FEET REQUIRE A PULL BOX / HANDBOLE / VAULT.
12. PULL BOX SHALL NOT BE USED IN LIEU OF A BEND. CONDUITS MUST RUN STRAIGHT THROUGH A PULL BOX WITH THE BEND LOCATED EITHER BEFORE OR AFTER THE PULL BOX.
13. PROVIDE COVERS WITH LABELING FOR JUNCTION BOXES, BACK BOXES WITHOUT FACEPLATES, AND PULL BOXES. LABELING SHALL INCLUDE THE CABLE TYPES AND THE APPLICABLE NUMBERING SCHEME FOR EACH CABLE CONTAINED WITHIN THE BOX. REFER TO SPECIFICATIONS FOR LABELING REQUIREMENTS.
14. IN OPEN CEILINGS, NON-ACCESSIBLE CEILING SPACE, MECHANICAL SPACES, AND ELEVATOR CONTROL ROOMS, ALL SIGNAL AND LOW VOLTAGE POWER CABLE TO BE ROUTED IN EMT CONDUIT. MINIMUM SIZE SHALL BE 1" SIZE PER NEC 40% FILL REQUIREMENT.
15. ROUTE CONDUIT WITH OTHER BUILDING SERVICES AND CONCEAL WHENEVER POSSIBLE. GROUP AND RUN PARALLEL ALONG A SINGLE BUILDING COLUMN LINE. HOLD TIGHT TO STRUCTURE AND PAINT AS DIRECTED BY THE ARCHITECT. UTILIZE STRUCTURALLY CONDUIT LEAVE OUTS IN LIEU OF ROUTING BELOW STRUCTURAL BEAMS.
16. FOR IN-SLAB UNDERGROUND CONDUIT ENTERING A BUILDING, TRANSITION BACK TO METALLIC CONDUIT WITHIN 3 FEET OF THE ENTRY POINT.
17. HORIZONTAL TELECOMMUNICATIONS/DATA CABLING SHALL MEET THE REQUIREMENTS OF ANSI/TIA568 AND SHALL NOT EXCEED 90 METERS (295 FT) OF TOTAL CABLE DISTANCE. CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFICATION OF 90 METER RULE.
18. LOW VOLTAGE CONTRACTOR SHALL PROVIDE AND INSTALL ALL REQUIRED SLEEVES FOR ROUTING OF LOW VOLTAGE CABLING. LOW VOLTAGE CONTRACTOR TO FIRE STOP ALL PENETRATIONS TO MAINTAIN RATING OF WALL. SEE DETAILS FOR EXACT REQUIREMENTS.
19. COORDINATE EXACT LOCATION OF VOICE/DATA, DATA, & TV OUTLETS WITH POWER RECEPTACLES.
20. WIRELESS ACCESS POINT FINAL QUANTITIES AND LOCATIONS TO BE DETERMINED THROUGH PREDICTIVE SURVEY ANALYSIS. SURVEY ANALYSIS SHALL BE SUBMITTED TO DESIGN TEAM FOR APPROVAL PRIOR TO DEVICE INSTALLATION.
21. COORDINATE ALL VIDEO SURVEILLANCE CAMERA LOCATIONS WITH FIELD CONDITIONS. CONTRACTOR TO VERIFY CLEAR FIELD OF VIEW AND SUBMIT RF FOR RELOCATION DUE TO OBSTRUCTION OF VIEWS.
22. FOR ALL EXTERIOR CAMERA LOCATIONS AND CABLING ROUTED THROUGH EXTERIOR WALLS, CONTRACTOR TO PROVIDE TRANSIENT VOLTAGE SURGE SUPPRESSION DEVICES (TVSS) FOR SIGNAL AND POWER CONDUCTORS TYPICAL TO DITEK-DTM-RPOE SURGE PROTECTOR AT ASSOCIATED TELECOM CLOSET.
23. REFERENCE SECURITY CAMERA SCHEDULES FOR VIEWS AND MOUNTING REQUIREMENTS. POSITION CAMERAS AS NOTED ON DRAWINGS THEN ADJUST AND FOCUS CAMERA VIEW TO SATISFACTION OF OWNER. COORDINATE LOCATIONS OF ALL VIDEO SURVEILLANCE CAMERAS WITH BUILDING SYSTEMS IN ORDER TO ENSURE CLEAR FIELD OF VIEW.
24. COORDINATE MEDIA CONVERSION DEVICE REQUIREMENTS, ELECTRICAL POWER, ANCILLARY ENCLOSURES, & COMPOSITE FIBER/COPPER CABLE LOCATIONS WITH DIVISION 27, COMPOSITE FIBER CABLING REQUIRED FOR VIDEO SURVEILLANCE CAMERAS LOCATED ON LIGHTING POLES AND AT LOCATIONS EXCEEDING 100 METERS FROM IDF/TELECOM ROOMS.
25. INTERFACE SECURITY AND ACCESS CONTROL SYSTEM POWER SUPPLIES WITH FIRE ALARM SYSTEM OUTPUTS. ALL DOORS TO RELEASE UPON FIRE ALARM SIGNAL, WHERE REQUIRED BY CODE.
26. SECURITY CONTRACTOR TO PROVIDE ALL LOCK POWER SUPPLIES AND INTERFACE TO ELECTRONIC DOOR HARDWARE FOR CONTROL.
27. CONTRACTOR TO COORDINATE WITH ARCHITECTURAL PLANS AND SPECIFICATIONS AS WELL AS LOCAL AHJ TO MAINTAIN EGRESS REQUIREMENTS.
28. ALL CONDUITS ROUTED BELOW GRADE TO BE SCHEDULE 40 PVC AND ALL CONDUITS ROUTED ABOVE GRADE TO BE EMT.
29. ALL CONDUITS ROUTED BELOW GRADE TO BE SEALED TO PREVENT WATER INFILTRATION INTO EQUIPMENT ROOMS.
30. ALL CONDUIT INSTALLED INDOORS AND BELOW CEILING TO BE PAINTED TO MATCH DECOR.
31. AS REQUIRED BY NATIONAL ELECTRIC CODE, NEC 300.5 (A), PROVIDE MINIMUM OF 24" OF COVER WHERE CONDUITS ARE CROSSING UNDER STREETS, ROADS, ALLEYS, DRIVEWAYS, AND PARKING AREAS.
32. CONTRACTOR SHALL UTILIZE RIGID CONDUIT ELBOWS FOR ALL 90° CONDUIT TURN-UPS FROM UNDERGROUND DUCT BANKS TO INTERIOR LOCATIONS.
33. REFERENCE VOICE AND DATA ONE-LINE DIAGRAMS FOR INSTALLATION REQUIREMENTS ASSOCIATED WITH REQUIRED BACKBONE CABLING SYSTEMS.
34. REFERENCE ELECTRICAL SPECIFICATIONS FOR DUCT BANK INSTALLATION REQUIREMENTS. ALL NEW EXTERIOR DUCTBANKS TO BE PROVIDED WITH METALLIC TRACER WIRE TO ALLOW FUTURE LOCATION.

DEVICE LEGEND - TELECOM/STRUCTURED CABLING						
SYMBOL	DEVICE	ROUGH-IN BOX	MOUNTING HEIGHT	CABLING QTY & TYPE	ELECTRICAL CONDUIT ROUGH-IN	DEVICE NOTES
□#	WALL MOUNT DATA OUTLET	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	18" AFF - UNO	(2) CATEGORY 6 - UNO	ONE(1) - 1" EMT CONDUIT, FOR MORE THAN 3 CABLES UPSIZE CONDUIT TO MEET NEC 40% FILL RATIO	#" NUMERICAL SUBSCRIPT DENOTES TOTAL NUMBER OF REQUIRED CABLES. SINGLE GANG TILE RING REQUIRED.
□C	WALL MOUNT DATA OUTLET ABOVE COUNTER	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	42" AFF - UNO	(2) CATEGORY 6 - UNO	ONE(1) - 1" EMT CONDUIT, FOR MORE THAN 3 CABLES UPSIZE CONDUIT TO MEET NEC 40% FILL RATIO	SINGLE GANG TILE RING REQUIRED
□TV	TELEVISION DATA OUTLET	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	...	(2) CATEGORY 6 - UNO	ONE(1) - 1" EMT CONDUIT	REFER TO AV DRAWINGS AND ARCHITECTURAL ELEVATIONS FOR BACK BOX HEIGHT AND TERMINATION / MOUNTING REQUIREMENTS
□#	CEILING WIRELESS ACCESS POINT DATA OUTLET	(2) CATEGORY 6A - UNO	ONE(1) - 1" EMT CONDUIT	PROVIDE 20' SERVICE LOOP SUPPORTED FROM J HOOKS SPACED 12" APART AND SUPPORTED FROM STRUCTURAL CEILING ABOVE
□#	FLOORBOX DATA OUTLET	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	...	(2) CATEGORY 6 - UNO	ONE(1) - 1" EMT CONDUIT	PROVIDE 20' SERVICE LOOP SUPPORTED FROM J HOOKS SPACED 12" APART AND SUPPORTED FROM STRUCTURAL CEILING ABOVE

SHEET LIST	
SHEET NUMBER	SHEET NAME
LV-000	COVER PAGE
LV-101	SITE PLAN
LV-201	LEVEL 1 - FLOOR PLAN
LV-301	LEVEL 1 - RCP
LV-401	LARGE SCALES - COMMUNICATIONS 120
LV-402	ONE-LINE DIAGRAMS
LV-501	ONE-LINE DIAGRAMS
LV-502	DETALS - CAMERAS
LV-503	DETALS - DOORS
LV-504	DETALS - FIRESTOPPING
LV-505	DETALS - GROUNDING
LV-506	DETALS - OUTLETS & INSTALLATION

CDH
ARCHITECTURE
330 Cumberland Blvd. SE
Suite 100
Atlanta, GA 30339
770.423.0016
www.cdppartners.com
COPYRIGHT © 2023 by CDH PARTNERS INC.
All rights reserved.

J&A
ENGINEERING CONSULTANTS
4094 LOWER ROSWELL RD
SUITE 100
MARIETTA, GEORGIA 30068
www.jaengineering.net

GRADY HEALTH SYSTEM
Center of Memorial Drive & Estoria Street
Atlanta GA 30316

NOT ISSUED FOR CONSTRUCTION

PROJECT NO: 25132.00
DD PACKAGE 12/18/2025

SHEET TITLE
COVER PAGE
SHEET NUMBER


LV-000

DEVICE LEGEND - SECURITY/ACCESS CONTROL (DEVICES PROVIDED & INSTALLED BY SECURITY CONTRACTOR)						
SYMBOL	DEVICE	ROUGH-IN BOX	MOUNTING HEIGHT	CABLING QTY & TYPE	ELECTRICAL CONDUIT ROUGH-IN	DEVICE NOTES
CR	MULTI-TECHNOLOGY CARD READER	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	42" AFF - UNO	22-18AWG, 6 CONDUCTOR TWISTED, OASHIELD	ONE(1) - 3/4" EMT CONDUIT TO SECURITY JUNCTION BOX IN ACCESSIBLE CEILING	SINGLE GANG TILE RING REQUIRED
ES	ELECTRIC DOOR STRIKE	18AWG, 2 CONDUCTOR & 22AWG, 4 CONDUCTOR	ONE(1) - 3/4" EMT CONDUIT FROM DOOR FRAME TO SECURITY JUNCTION BOX IN ACCESSIBLE CEILING	ELECTRONIC STRIKE HARDWARE AND TRANSFER HINGE BY DIVISION 8; POWER SUPPLY PROVIDED AND INSTALLED BY SECURITY CONTRACTOR.
E	ELECTRIC DOOR HARDWARE	18AWG, 2 CONDUCTOR & 22AWG, 4 CONDUCTOR	ONE(1) - 3/4" EMT CONDUIT FROM DOOR FRAME TO SECURITY JUNCTION BOX IN ACCESSIBLE CEILING	ELECTRONIC LOCKING HARDWARE W/INTEGRATED REQUEST TO EXIT POWER SUPPLY PROVIDED AND INSTALLED BY SECURITY CONTRACTOR.
P	DOOR POSITION SWITCH	22AWG, 2 CONDUCTOR	ONE(1) - 3/4" EMT CONDUIT FROM DOOR FRAME TO SECURITY JUNCTION BOX IN ACCESSIBLE CEILING	SINGLE-POLE/ DOUBLE-THROW DOOR POSITION SENSORS PROVIDED, INSTALLED AND WIRED BY SECURITY CONTRACTOR.
DB	DURESS BUTTON	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	COORDINATE WITH FURNITURE	22AWG, 2 CONDUCTOR	ONE(1) - 3/4" FLEX CONDUIT TO WALL MOUNT J BOX AND ONE(1) - 3/4" EMT CONDUIT TO ACCESSIBLE CEILING	PROVIDE MIN 6 FT ARMORED CABLING SERVICE LOOP TO WALL MOUNT J BOX. COORDINATE WITH FURNITURE FOR EXACT BUTTON PLACEMENT.
■	ADA DOOR ACTUATOR BUTTON	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	48" AFF - UNO	22AWG, 4 CONDUCTOR	ONE(1) - 3/4" EMT CONDUIT	COORDINATE WITH DIVISION 8 FOR INTERFACE TO SHUNT DOOR OPERATOR BUTTON UNTIL VALID CARD READ. SINGLE GANG TILE RING REQUIRED.

DEVICE LEGEND - INTRUSION DETECTION (DEVICES PROVIDED & INSTALLED BY SECURITY CONTRACTOR)						
SYMBOL	DEVICE	ROUGH-IN BOX	MOUNTING HEIGHT	CABLING QTY & TYPE	ELECTRICAL CONDUIT ROUGH-IN	DEVICE NOTES
KP	INTRUSION KEYPAD/ANNUNCIATOR	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	54" AFF - UNO	(1) 22AWG, 4 CONDUCTOR, STRANDED, UNSHIELDED	ONE(1) - 3/4" EMT CONDUIT	SINGLE GANG TILE RING REQUIRED
MD	360° MOTION DETECTOR (CEILING MOUNTED)	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	...	22AWG, 2 CONDUCTOR	ONE(1) - 3/4" EMT CONDUIT	ROUTE SIGNAL AND POWER TO INTRUSION DETECTION SYSTEM IN DEDICATED RACEWAY. SINGLE GANG TILE RING REQUIRED
GB	GLASS BREAK DETECTOR	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	...	22AWG, 2 CONDUCTOR	ONE(1) - 3/4" EMT CONDUIT	ROUTE SIGNAL AND POWER TO INTRUSION DETECTION SYSTEM IN DEDICATED RACEWAY. SINGLE GANG TILE RING REQUIRED

DEVICE LEGEND - VIDEO SURVEILLANCE (DEVICES & MOUNTING HARDWARE PROVIDED & INSTALLED BY SECURITY CONTRACTOR)						
SYMBOL	DEVICE	ROUGH-IN BOX	MOUNTING HEIGHT	CABLING QTY & TYPE	ELECTRICAL CONDUIT ROUGH-IN	DEVICE NOTES
□	SINGLE SENSOR FIXED CAMERA	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	SEE FLOOR PLANS	(1) CATEGORY 6 - BY TELECOM CONTRACTOR	ONE(1) - 1" EMT CONDUIT	ELECTRICAL ROUGH-IN ONLY REQUIRED FOR INACCESSIBLE AND OPEN CEILINGS. SINGLE GANG TILE RING REQUIRED. REFER TO CAMERA INSTALLATION DETAILS AND SCHEDULE FOR FURTHER REQUIREMENTS.
□	DUAL SENSOR FIXED CAMERA	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	SEE FLOOR PLANS	(1) CATEGORY 6 - BY TELECOM CONTRACTOR	ONE(1) - 1" EMT CONDUIT	ELECTRICAL ROUGH-IN ONLY REQUIRED FOR INACCESSIBLE AND OPEN CEILINGS. SINGLE GANG TILE RING REQUIRED. REFER TO CAMERA INSTALLATION DETAILS AND SCHEDULE FOR FURTHER REQUIREMENTS.
□	MULTI SENSOR (3) FIXED CAMERA	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	SEE FLOOR PLANS	(1) CATEGORY 6 - BY TELECOM CONTRACTOR	ONE(1) - 1" EMT CONDUIT	ELECTRICAL ROUGH-IN ONLY REQUIRED FOR INACCESSIBLE AND OPEN CEILINGS. SINGLE GANG TILE RING REQUIRED. REFER TO CAMERA INSTALLATION DETAILS AND SCHEDULE FOR FURTHER REQUIREMENTS.
□	MULTI SENSOR (4) FIXED CAMERA	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	SEE FLOOR PLANS	(1) CATEGORY 6 - BY TELECOM CONTRACTOR	ONE(1) - 1" EMT CONDUIT	ELECTRICAL ROUGH-IN ONLY REQUIRED FOR INACCESSIBLE AND OPEN CEILINGS. SINGLE GANG TILE RING REQUIRED. REFER TO CAMERA INSTALLATION DETAILS AND SCHEDULE FOR FURTHER REQUIREMENTS.
□	FISH-EYE CAMERA	4" SQUARE BACKBOX W/ SINGLE GANG TILE RING	SEE FLOOR PLANS	(1) CATEGORY 6 - BY TELECOM CONTRACTOR	ONE(1) - 1" EMT CONDUIT	ELECTRICAL ROUGH-IN ONLY REQUIRED FOR INACCESSIBLE AND OPEN CEILINGS. SINGLE GANG TILE RING REQUIRED. REFER TO CAMERA INSTALLATION DETAILS AND SCHEDULE FOR FURTHER REQUIREMENTS.

COMMON ABBREVIATIONS:	
ADA	AMERICANS WITH DISABILITIES ACT
AFC	ABOVE FINISHED CEILING
AFF	ABOVE FINISHED FLOOR
AGF	ABOVE FINISHED GRADE



SITE PLAN

1" = 20'-0"

1" = 20

GENERAL NOTES:

- A. AS REQUIRED BY NATIONAL ELECTRIC CODE, NEC 300.5 (A), PROVIDE MINIMUM OF 24" OF COVER WHERE CONDUITS ARE CROSSING UNDER STREET, ROADS, ALLEYS, DRIVEWAYS, AND PARKING AREAS.
- B. ALL EXTERIOR UNDERGROUND CONDUIT PATHWAYS TO BE PROVIDED WITH METALLIC TRACER WIRE TO ALLOW FUTURE LOCATION.
- C. ALL CONDUITS ROUTED BELOW GRADE TO BE SEALED TO PREVENT WATER INFILTRATION INTO EQUIPMENT ROOMS.
- D. THE CONTRACTOR SHALL UTILIZE RIGID CONDUIT ELBOWS FOR ALL 90° CONDUIT TURN-UPS FROM UNDERGROUND DUCTS BANKS TO INTERIOR LOCATIONS.
- E. ALL SLAB AND CMU BLOCK WALL PENETRATIONS TO BE FIRE-PROOFED AND SEALED.
- F. ALL UNDERGROUND CABLING TO BE OSP RATED.
- G. FOR COPPER CABLES, GROUND WITH PROTECTOR BLOCKS AT THE TRANSITION BETWEEN OUTSIDE PLANT AND INSIDE PLANT CABLING.
- H. ALL SITE HANDHOLE LOCATIONS TO BE COORDINATED WITH LANDSCAPE ARCHITECT FOR PLACEMENT IN CONCEALED LOCATIONS (EX. PINESTRAW BED, MULCH BED, ETC). HANDHOLES SHALL NOT BE LOCATED IN HARDSCAPE.
- I. ALL DAMAGED LANDSCAPING, ASPHALT, AND CONCRETE SHALL BE RETURNED BACK TO THE ORIGINAL CONDITION.

KEY NOTES:

- ① CONTRACTOR TO PROVIDE AND INSTALL QUAZITE 30"X60" PG STYLE POLYMER CONCRETE ASSEMBLY WITH 2 BOLT, TIER 15 LID, STANDARD OPEN BOTTOM 30" DEEP BOX. BOX SHALL BE TYPICAL TO PART #PG3060BA30 AND LID SHALL BE TYPICAL TO PART #PG3060HA0012. SEE INSTALLATION DETAIL FOR COMPLETE REQUIREMENTS.
- ② CONTRACTOR TO PROVIDE AND INSTALL QUAZITE 11"X18" PG STYLE POLYMER CONCRETE ASSEMBLY WITH 2 BOLT, TIER 15 LID, STANDARD OPEN BOTTOM 18" DEEP BOX. BOX SHALL BE TYPICAL TO PART #PG1118BA18 AND LID SHALL BE TYPICAL TO PART #PG1118HA0012. SEE INSTALLATION DETAIL FOR COMPLETE REQUIREMENTS.
- ③ CONTRACTOR TO INSTALL BELOW GRADE, ONE (1)-1.5" SCHEDULE 40 PVC CONDUITS BETWEEN HANDHOLE AND STUB INTO BASE OF EMERGENCY CALL STANCHION/CAMERA POLE PER NEC CODE REQUIREMENTS. ALL CONDUIT OPENINGS ARE TO BE SEALED TO PREVENT WATER INFILTRATION.
- ④ CONTRACTOR TO INSTALL BELOW GRADE, TWO (2)-2" SCHEDULE 40 PVC CONDUITS BETWEEN HANDHOLE AND STUB INTO IT COMM ROOM PER NEC CODE REQUIREMENTS. ALL CONDUIT OPENINGS ARE TO BE SEALED TO PREVENT WATER INFILTRATION.

GRADY ESTORIA URGENT CARE


GRADY HEALTH SYSTEM

GRADY HEALTH SYSTEM — ORIA URG

NOT ISSUED FOR
CONSTRUCTION

SHEET TITLE
SITE PLAN

SHEET NUMBER
LV-101

SHEET TITLE
LEVEL 1 -
FLOOR PLAN

GENERAL NOTES:

- A. ALL LOW VOLTAGE CONTRACTORS SHALL BE REQUIRED TO PARTICIPATE IN CEILING COORDINATION MEETINGS ALONG WITH OTHER SPECIALTIES AND CONTRACTOR TRADES.
- B. COORDINATE EXACT LOCATION AND ORIENTATION OF VOICE/DATA, CATV, AND DATA OUTLETS WITH POWER RECEPTACLES. DATA OUTLETS TO MATCH POWER RECEPTACLE ORIENTATION AND ELEVATION.
- C. ALL INTERIOR LOW VOLTAGE CABLES SHALL BE PLENUM RATED. IN OPEN CEILINGS AND CEILING SPACES THAT ARE NOT ACCESSIBLE, CABLES SHALL BE ROUTED IN EMT CONDUIT. MINIMUM SIZE SHALL BE 3/4". SIZE ALL CONDUIT PER NEC 40% FILL REQUIREMENT.
- D. ALL CONDUIT INSTALLATION TO MEET REQUIREMENTS OF NATIONAL ELECTRIC CODE (NEC) CURRENT EDITION.
- E. FOR ALL LOW VOLTAGE CABLEING, PROVIDE EMT RACEWAY FROM DEVICE BACKBOX TO ACCESSIBLE CEILING SPACE, WITH J-HOOK SUPPORT TO NEAREST CORRIDOR J-HOOKTREE SUPPORT SYSTEM. J-HOOKS SHALL BE INSTALLED ON 4'-0" TO 5'-0" CENTERS.
- F. CONDUIT SLEEVES TO BE PROVIDED FOR ALL LOW VOLTAGE CABLEING ROUTED ABOVE GYPSUM OR INACCESSIBLE CEILING LOCATION. SLEEVES SHALL BE SIZED FOR MAXIMUM 40% FILL REQUIREMENT.
- G. THE J-HOOK PATHWAY FOR HORIZONTAL LOW VOLTAGE CABLES SHALL BE COORDINATED WITH OTHER TRADES, PLACEMENT SHALL ALLOW FUTURE ACCESS AND LINE UP WITH FIREWALL PENETRATIONS.
- H. ALL VOICE, DATA, & CATV CABLES TO BE ROUTED DIRECT TO TELECOM ROOM WITHOUT SPLICES. NO JUNCTIONS OR SPLICES IN CABLES ARE ACCEPTABLE.
- I. REFERENCE DETAIL SHEETS FOR DEVICE MOUNTING REQUIREMENTS AND ADDITIONAL INFORMATION. COORDINATE THE LOCATION AND MOUNTING HEIGHT OF LOW VOLTAGE DEVICES WITH THE ARCHITECTURAL FLOOR PLANS AND ELEVATION DRAWINGS.
- J. REFERENCE CAMERA SCHEDULE FOR VIEWS AND MOUNTING REQUIREMENTS. ALL CAMERA VIEWS SHALL BE COORDINATED AND APPROVED BY THE OWNER'S DIRECTOR OF SECURITY OPERATIONS.

KEY NOTES:

- ① CONTRACTOR TO INTEGRATE REQUEST-TO-EXIT SIGNAL FROM ELECTRIC DOOR HARDWARE AND DOOR POSITION SWITCH INTO ACCESS CONTROL SYSTEM. REQUEST-TO-EXIT SIGNAL SHALL SHUNT DOOR ALARM.
- ② DOOR TO BE CONTROLLED ON SCHEDULE FOR LOCK/UNLOCK THROUGH SECURITY AND ACCESS CONTROL SCHEDULING FUNCTIONALITY. COORDINATE WITH OWNER FOR EXACT SCHEDULING REQUIREMENTS.
- ③ FLAT PANEL DISPLAY LOCATION. OWNER PROVIDED AND CONTRACTOR INSTALLED FLAT PANEL DISPLAY. GENERAL CONTRACTOR TO PROVIDE WALL BLOCKING FOR DISPLAY. SEE ELEVATIONS FOR EXACT REQUIREMENTS.
- ④ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL ONE(1) 120V/20A POWER OUTLET ADJACENT TO DATA OUTLET. COORDINATE EXACT HEIGHT WITH ARCHITECTURAL ELEVATIONS.
- ⑤ DATA OUTLET FOR PRINTER LOCATION. COORDINATE WITH ARCHITECTURAL ELEVATIONS FOR EXACT HEIGHT. MOUNT ADJACENT TO POWER RECEPTACLE.
- ⑥ DATA OUTLET FOR FUTURE WEAPONS DETECTION SYSTEM. CONTRACTOR TO MOUNT TO FLOOR BASEBOARD MULLION. ELECTRICAL CONTRACTOR TO PROVE POWER RECEPTACLE ADJACENT TO DATA.

P

N

M

L

K

J

H

G

F


E

D

C

B

A




GENERAL NOTES:

- A. ALL LOW VOLTAGE CONTRACTORS SHALL BE REQUIRED TO PARTICIPATE IN CEILING COORDINATION MEETINGS ALONG WITH OTHER SPECIALTIES AND CONTRACTOR TRADES.
- B. COORDINATE EXACT LOCATION AND ORIENTATION OF VOICE/DATA,CATV, AND DATA OUTLETS WITH POWER RECEPTACLES. DATA OUTLETS TO MATCH POWER RECEPTACLE ORIENTATION AND ELEVATION.
- C. ALL INTERIOR LOW VOLTAGE CABLES SHALL BE PLENUM RATED IN OPEN CEILINGS AND CEILING SPACES THAT ARE NOT ACCESSIBLE. CABLES SHALL BE ROUTED IN EMT CONDUIT. MINIMUM SIZE SHALL BE 3/4", SIZE ALL CONDUIT PER NEC 40% FILL REQUIREMENT.
- D. ALL CONDUIT INSTALLATION TO MEET REQUIREMENTS OF NATIONAL ELECTRIC CODE (NEC) CURRENT EDITION.
- E. FOR ALL LOW VOLTAGE CABLEING, PROVIDE EMT RACEWAY FROM DEVICE BACKBOX TO ACCESSIBLE CEILING SPACE, WITH J-HOOK SUPPORT TO NEAREST CORRIDOR J-HOOK TREE SUPPORT SYSTEM. J-HOOKS SHALL BE INSTALLED ON 4'-0" TO 5'-0" CENTERS.
- F. THE J-HOOK PATHWAY FOR HORIZONTAL LOW VOLTAGE CABLES SHALL BE COORDINATED WITH OTHER TRADES. PLACEMENT SHALL ALLOW FUTURE ACCESS AND LINE UP WITH FIREWALL PENETRATIONS.
- G. ALL VOICE, DATA, & CATV CABLES TO BE ROUTED DIRECT TO TELECOM ROOM WITHOUT SPLICES. NO JUNCTIONS OR SPLICES IN CABLES ARE ACCEPTABLE.
- H. REFERENCE DETAIL SHEETS FOR DEVICE MOUNTING REQUIREMENTS AND ADDITIONAL INFORMATION. COORDINATE THE LOCATION AND MOUNTING HEIGHT OF LOW VOLTAGE DEVICES WITH THE ARCHITECTURAL FLOOR PLANS AND ELEVATION DRAWINGS.
- I. REFERENCE CAMERA SCHEDULE FOR VIEWS AND MOUNTING REQUIREMENTS. ALL CAMERA VIEWS SHALL BE COORDINATED AND APPROVED BY THE OWNER'S DIRECTOR OF SECURITY OPERATIONS.
- J. THE CONTRACTOR IS RESPONSIBLE FOR CORING FURNITURE FEED THROUGHS REQUIRED FOR DATA PATHWAYS TO FINAL EQUIPMENT LOCATIONS. COORDINATE EQUIPMENT PLACEMENT REQUIRING FEEDTHROUGHS AND DESKTOP GROMMETS WITH THE OWNER FOR LOCATIONS.

PROJECT NO: 25132.00
DD PACKAGE 12/18/2025

NOT ISSUED FOR
CONSTRUCTION



SHEET TITLE
LEVEL 1 - RCP

SHEET NUMBER

LV-211

P

N

M

L

K

J

H

G

F

E


D

C

B

A

12/17/2025 2:24:24 PM



P

N

M

L

K

J

H

G

F


E

D

C

B

A



GENERAL NOTES:


- A. THE ELECTRICAL CONTRACTOR SHALL PROVIDE AND INSTALL UL CERTIFIED FIRESTOP SYSTEM UTILIZING STI EZ PATH SERIES. PROVIDE EZ PATH SLEEVES WHERE NECESSARY TO ROUTE CABLES THROUGH ALL FIRE AND SMOKE WALLS. MAINTAIN A MINIMUM OF 25% CAPACITY IN EACH SLEEVE AT THE CLOSE OF THE PROJECT.
- B. THE LV CONTRACTOR SHALL COORDINATE WITH THE GRADY IT TEAM FOR EXACT RACK ARRANGEMENT AND LOCATION OF ALL DEVICES PRIOR TO ORDERING EQUIPMENT.
- C. LV CONTRACTOR SHALL KEEP THE MDF AND IDF ROOMS ORGANIZED, FREE OF CLUTTER, DEBRIS AND DUST. A DAILY CLEANING SHALL BE PERFORMED OVER THE COURSE OF THE PROJECT. THE CONTRACTOR SHALL PROVIDE THE FINAL CLEANING OF THE IT ROOMS.
- D. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL PATCHING BETWEEN FIBER, CAT 6, AND CAT 6A PATCH PANELS AND ACTIVE EQUIPMENT PROVIDED BY THE OWNER. THE CONTRACTOR MUST COORDINATE WITH THE OWNER'S IT PROJECT MANAGER TO DETERMINE THE EXACT PATCHING ARRANGEMENT BEFORE ORDERING PATCH CABLES.

KEY NOTES:

- ① CONTRACTOR TO PROVIDE TIA/EIA STANDARD 2-POST 84"X 19" OPEN FRAME RELAY RACK. RACK TO BE PROVIDED WITH TWO-SIDED VERTICAL WIRE MANAGER. SEE DETAIL FOR TYPICAL RACK ELEVATION. RACK TO BE TYPICAL TO CPI #5053-715.
- ② TELECOM CONTRACTOR TO PROVIDE AND INSTALL VERTICAL CABLE MANAGER, DOUBLE-SIDED, 84" HIGH X 6" WIDE X 24.5" DEEP. CABLE MANAGER TO BE TYPICAL TO CPI #3552-703.
- ③ TELECOM CONTRACTOR TO PROVIDE AND INSTALL 18" HORIZONTAL LADDER RACK INSTALLED AT 90° AFF. LADDER RACK TO BE PROVIDED WITH TURN-DOWN VANES ABOVE VERTICAL WIRE MANAGERS. COORDINATE FINAL LADDER RACK LAYOUT WITH OWNER, PRIOR TO ORDERING LADDER RACK TO BE TYPICAL TO CPI #10250-718. PROVIDE ALL BUTT-SPICE AND JUNCTION SPLICING KITS AT INTERSECTION AND TERMINATIONS.
- ④ GENERAL CONTRACTOR TO PROVIDE AND INSTALL 8" HIGH X 3/4" THICK FIRE RATED PLYWOOD BACKBOARDS INSTALLED AT 8" AFF ON ALL FOUR WALLS, BOTH SIDES AND ALL EDGES SHALL BE TREATED WITH TWO(2) COATS OF FIRE RETARDANT GREY PAINT. FIRE RATED STAMP SHALL BE LEFT UNPAINTED.
- ⑤ ELECTRICAL CONTRACTOR TO PROVIDE DEDICATED 120 VAC, 20A, POWER RECEPTACLES INSIDE SECURITY CABINETS. COORDINATE EXACT PLACEMENT WITH EQUIPMENT LOCATION.
- ⑥ ELECTRICAL CONTRACTOR FURNISHED AND INSTALLED GROUNDBAR INSTALLED AT 84" AFF. REFER TO GROUNDING DETAILS FOR ADDITIONAL INFORMATION. BUSBAR TO BE TYPICAL TO CPI #10622 SERIES.
- ⑦ PROVIDE THREE(3) - 4" STI EZ-PATH 44+ SERIES SLEEVES WITH GANG PLATE FOR ROUTING HORIZONTAL LOW VOLTAGE CABLING AND LINE UP SLEEVES WITH HORIZONTAL LADDER RACK.
- ⑧ ELECTRICAL CONTRACTOR TO PROVIDE ONE(1) LG-30R, 30 AMP, 120 VAC POWER RECEPTACLE WITH NEMA TWIST LOCK CONNECTOR ON NORMAL POWER. MOUNT ON HORIZONTAL LADDER RACK ABOVE VERTICAL CABLE MANAGER.
- ⑨ ELECTRICAL CONTRACTOR TO PROVIDE ONE(1) 5-20R, 20 AMP, 120 VAC POWER RECEPTACLE MOUNT IN QUAD POWER RECEPTACLE ON NORMAL POWER. MOUNT ON HORIZONTAL LADDER RACK ABOVE VERTICAL CABLE MANAGER.

RACK ELEVATION IS FOR ILLUSTRATIVE PURPOSES ONLY.
CONTRACTOR TO VERIFY QUANTITY OF RACK EQUIPMENT
REQUIRED TO PROVIDE FULL COVERAGE.

LEGEND:	
FCP	FIBER OPTIC PATCH PANEL
HORIZONTAL WIRE MANAGER (2RMU)	
48-PORT CATEGORY 6 PATCH PANEL (2RMU)	
CAT 6A	24-PORT CATEGORY 6A PATCH PANEL (2RMU)
OWNER PROVIDED UPS	




1 ONE-LINE DIAGRAM - ACCESS CONTROL SYSTEM
N.T.S.

KEY NOTES:

(APPLIES TO THIS DETAIL ONLY)

- VERIFY AND PROVIDE EXACT QUANTITY OF CARD READERS, DOOR POSITION SWITCH INPUTS, DOOR RELEASE BUTTONS, DURESS BUTTONS, AND MISCELLANEOUS SIGNAL INPUTS AS SHOWN ON CONTRACT DRAWINGS.
- SECURITY CONTRACTOR TO INTERFACE WITH ELECTRIC AND ELECTROMAGNETIC LOCKS PER THE CONTRACT SPECIFICATIONS. CONTRACTOR TO INTEGRATE ALL CONTROLLED OUTPUTS INTO ACCESS CONTROL SYSTEM. VERIFY QUANTITY OF ALL CONTROLLED OUTPUTS WITH CONTRACT DRAWINGS.
- SECURITY CONTRACTOR TO COORDINATE WITH FIRE ALARM CONTRACTOR FOR FIRE ALARM CONTACT CLOSURE FROM FIRE ALARM RELAY SIGNAL. CONTRACTOR TO CONNECT RELAY SIGNAL TO DOOR HARDWARE POWER SUPPLY FOR IMMEDIATE RELEASE OF ELECTROMAGNETIC LOCKS UPON ACTIVATION OF THE FIRE ALARM SIGNAL.
- SECURITY CONTRACTOR TO INTERFACE WITH BUILDING SECURITY NETWORK BY PROVIDING CATEGORY 6 DATA CABLES BETWEEN ACCESS CONTROL PANELS AND OWNER PROVIDED NETWORK SWITCH.
- PROVIDE BATTERY BACK-UP EQUIPMENT AT EACH READER INTERFACE PANEL TO SUPPORT THE ACS FOR A PERIOD OF 30 MINUTES.
- CONTRACTOR TO UPDATE ACCESS CONTROL SOFTWARE CLIENT AND VMS/NVR CLIENT SOFTWARE ON UP TO THREE OWNER PROVIDED WORKSTATIONS. WORKSTATION LOCATIONS TO BE DETERMINED. VIDEO SURVEILLANCE AND ACCESS CONTROL SOFTWARE SHALL BOTH BE INSTALLED ON SAME PCS.
- CONTRACTOR SHALL EXPAND EXISTING ACCESS CONTROL SYSTEM TO INCLUDE NEW DOORS AND DEVICES ADDED TO THE AREA. PROVIDE ALL REQUIRED LICENSES FOR COMPLETE AND FULLY FUNCTIONAL SYSTEM. COORDINATE WITH OWNER TO DETERMINE AND PROVIDE ALL REQUIRED SOFTWARE UPDATES.
- CONTRACTOR TO PROGRAM ACCESS CONTROL SERVER. CONTRACTOR TO INTEGRATE THE VIDEO SURVEILLANCE SYSTEM WITH THE ACCESS CONTROL SYSTEM. PROVIDE SERIAL OR DISCREET OUTPUT TO VIDEO SURVEILLANCE EQUIPMENT FOR AUTOMATIC CAMERA CALL-UP.
- CONTRACTOR TO PROVIDE INTERCONNECTION OF ACCESS CONTROL LOCK OUTPUTS WITH LOCK POWER SUPPLY FOR INDIVIDUAL LOCK RELEASE.
- SECURITY CONTRACTOR TO PROVIDE, INSTALL AND PROGRAM ACCESS CONTROL BADGING WORKSTATION. LOCATION TO BE CONFIRMED WITH OWNER. SEE SPECIFICATIONS FOR REQUIREMENTS.
- COORDINATE WITH AUTO OPERATED DOOR HARDWARE VENDOR FOR OPERATION OF DOORS. ACCESS CONTROL HARDWARE SHALL RELEASE LOCKS PRIOR TO DOOR OPERATOR ACTIVATION.
- INTEGRATE DOORS SERVED BY THE VIDEO INTERCOM SUBSTATION WITH ACCESS CONTROL SYSTEMS. PROVIDE 18/2 CABLE TO ACS SYSTEM IN TELECOM ROOM TO INTERCOM INTERFACE OUTPUT MODULE FOR REMOTE DOOR RELEASE.




2 ONE-LINE DIAGRAM - DATA DISTRIBUTION
N.T.S.

KEY NOTES:

(APPLIES TO THIS DETAIL ONLY)

- FOR HORIZONTAL DATA CIRCUITS, PROVIDE 23 AWG/CATEGORY 6, 4 PR. CABLE FROM CATEGORY 6 PATCH PANEL IN TELECOM ROOMS TO STATION OUTLET LOCATIONS. SEE LEGEND AND FLOOR PLANS FOR REQUIREMENTS.
- REFERENCE OUTLET DETAILS FOR TERMINATION REQUIREMENTS.
- COPPER PATCH PANELS TO BE SIZED AS REQUIRED TO PROVIDE CAT. 6 LINK TO ALL STATION OUTLETS. PROVIDE SPARE CAPACITY AS REQUIRED IN SPECIFICATIONS. PATCH PANELS TO BE CATEGORY 6, 48 PORT, 1U, FLAT, HIGH DENSITY TYPE. PROVIDE 18' CABLE SLACK TO ALLOW FUTURE REPOSITIONING OF PATCH PANEL.
- PROVIDE 2-METER CATEGORY 6/6A PATCH CORDS FOR EACH TERMINATED HORIZONTAL CAT 6/6A CIRCUIT.
- COPPER PATCH PANELS TO BE SIZED AS REQUIRED TO PROVIDE CAT. 6A LINK TO ALL WIFI DATA OUTLETS. PROVIDE SPARE CAPACITY AS REQUIRED IN SPECIFICATIONS. PATCH PANELS TO BE CATEGORY 6A, 1U, HIGH DENSITY TYPE. PROVIDE 10' CABLE SLACK IN CLOSET TO ALLOW FUTURE REPOSITIONING OF PATCH PANEL.
- FOR WIFI DATA OUTLET, PROVIDE 23 AWG/CATEGORY 6A COMPLIANT/4 PR. STP CABLE FROM CATEGORY 6A PATCH PANEL IN TELECOM ROOMS TO ACCESS POINT OUTLET LOCATIONS. SEE LEGEND AND FLOOR PLANS FOR REQUIREMENTS.
- OWNER PROVIDED AND INSTALLED NETWORK SWITCHES.
- RACK MOUNT FIBER OPTIC CONNECTOR PANEL. ALL FIBER OPTIC STRANDS TO BE TERMINATED AND TESTED.
- PROVIDE 2-METER SINGLE MODE PATCH CORDS FOR EACH TERMINATED FIBER OPTIC STRAND.
- THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL PATCHING BETWEEN FIBER, CAT 6, AND CAT 6A PATCH PANELS AND ACTIVE EQUIPMENT PROVIDED BY THE OWNER. THE CONTRACTOR MUST COORDINATE WITH THE OWNER'S IT PROJECT MANAGER TO DETERMINE THE EXACT PATCHING ARRANGEMENT BEFORE ORDERING PATCH CABLES.




3 ONE-LINE DIAGRAM - INTRUSION DETECTION SYSTEM
N.T.S.

KEY NOTES:

(APPLIES TO THIS DETAIL ONLY)

- CONTRACTOR TO PROVIDE AND INSTALL ONE(1) CATEGORY 6 CABLE FOR EACH IP DEVICE.
- CONTRACTOR TO PROVIDE AND INSTALL LOW LIGHT, WIDE DYNAMIC RANGE (WDR), COLOR, IP MEGAPIXEL CAMERAS FOR INTERIOR LOCATIONS. SEE FLOOR PLANS FOR LOCATIONS. SEE CAMERA SCHEDULE FOR MOUNTING REQUIREMENTS. SEE SPECIFICATIONS FOR CAMERA REQUIREMENTS.
- CONTRACTOR TO PROVIDE AND INSTALL LOW LIGHT, WIDE DYNAMIC RANGE (WDR), COLOR, IP MEGAPIXEL CAMERAS WITH WEATHERPROOF HOUSINGS FOR EXTERIOR LOCATIONS. PROVIDE SURGE PROTECTION DEVICE AT CAMERA LOCATION TYPICAL TO DITEK DTK-MR10POE. SEE FLOOR PLANS FOR LOCATIONS. SEE CAMERA SCHEDULE FOR MOUNTING REQUIREMENTS. PROVIDE TRANSIENT VOLTAGE SURGE PROTECTION FOR ALL EXTERIOR CAMERAS AT PATCH PANEL AND AT CAMERA LOCATION.
- THE CONTRACTOR SHALL PROVIDE ALL REQUIRED LICENSING AND STORAGE FOR NEW VIDEO SURVEILLANCE CAMERAS.
- EACH CAMERA TO BE PROVIDED WITH 60 DAYS OF ON BOARD STORAGE. EACH CAMERA TO BE PROVIDED WITH A 5-YEAR LICENSE. CONTRACTOR TO COORDINATE WITH MANUFACTURER FOR START OF LICENSE TO START AT MATERIAL COMPLETION, NOT DATE OF PURCHASE.
- ALL CAMERA SETTINGS & VIEWS TO BE PROGRAMMED & CONFIGURED BY CONTRACTOR TO OWNER'S SATISFACTION.
- CONTRACTOR TO PROVIDE AND INSTALL ALL CATEGORY 6 PATCH CABLES.
- CONTRACTOR TO COORDINATE WITH TELECOM CONTRACTOR FOR UTILIZATION OF DATA INFRASTRUCTURE TO ESTABLISH CONNECTION TO THE SECURITY NETWORK VLAN.
- CONTRACTOR TO PROVIDE AND INSTALL POWER-OVER-ETHERNET SWITCH MOUNTED IN TELECOM RACK FOR VIDEO SURVEILLANCE SYSTEM.
- CONTRACTOR TO INSTALL DITEK, POE, RACK MOUNTED SURGE PROTECTORS FOR ALL OUTDOOR CAMERAS TYPICAL TO DITEK DTK.RM12POE.
- ALL EXTERIOR CAMERAS TO BE PROVIDED WITH TVSS DEVICES ON POWER & VIDEO SIGNAL ON CAMERA END TYPICAL TO DITEK MR10POE DEVICES.



4 ONE-LINE DIAGRAM - TV DISTRIBUTION
N.T.S.


KEY NOTES:

(APPLIES TO THIS DETAIL ONLY)

- ALL HORIZONTAL CATV CABLES TO BE PLUMED RATED RG-6U QUAD SHIELD TYPE FOR CABLING DISTANCES UP TO 150'-0". FOR CABLING DISTANCES LONGER THAN 150'-0", PROVIDE PLUMED RATED RG-11U QUAD SHIELD TYPE CABLE. PROVIDE SELF TERMINATING F-CONNECTOR AT EACH DESIGNATED OUTLET. SEE SPECIFICATIONS FOR COMPLETE REQUIREMENTS.
- REFERENCE OUTLET DETAILS FOR TERMINATION REQUIREMENTS.
- REFERENCE FLOOR PLAN DRAWINGS FOR CORRECT QUANTITY OF OUTLETS. CONFIRM INDIVIDUAL CABLE LENGTHS TO ALLOW PROPER BALANCING OF CATV SYSTEM.
- CONTRACTOR TO PROVIDE NEW SPLITTERS AND TAPS AS REQUIRED BY NEW CATV OUTLETS. COORDINATE WITH FLOOR PLANS. REQUIREMENT IS TO MAINTAIN 0 TO 10 dBmV OF SIGNAL AT EACH OUTLET.

KEY NOTES: (APPLIES TO THIS DETAIL ONLY)

- ① CONTRACTOR TO PROVIDE AND INSTALL ONE(1) CATEGORY 6 CABLE FOR EACH IP DEVICE.
- ② CONTRACTOR TO PROVIDE AND INSTALL LOW LIGHT, WIDE DYNAMIC RANGE (WDR), COLOR, IP MEGAPIXEL CAMERAS FOR INTERIOR LOCATIONS. SEE FLOOR PLANS FOR LOCATIONS. SEE CAMERA SCHEDULE FOR MOUNTING REQUIREMENTS. SEE SPECIFICATIONS FOR CAMERA REQUIREMENTS.
- ③ CONTRACTOR TO PROVIDE AND INSTALL LOW LIGHT, WIDE DYNAMIC RANGE (WDR), COLOR, IP MEGAPIXEL CAMERAS FOR EXTERIOR LOCATIONS. SEE FLOOR PLANS FOR LOCATIONS. SEE CAMERA SCHEDULE FOR MOUNTING REQUIREMENTS. PROVIDE SURGE PROTECTION DEVICE AT CAMERA LOCATION TYPICAL TO DITEK DTK-MRIPOE. SEE FLOOR PLANS FOR LOCATIONS. SEE CAMERA SCHEDULE FOR MOUNTING REQUIREMENTS. PROVIDE TRANSIENT VOLTAGE SURGE PROTECTION FOR ALL EXTERIOR CAMERAS AT PATCH PANEL AND AT CAMERA LOCATION.
- ④ THE CONTRACTOR SHALL PROVIDE ALL REQUIRED LICENSING AND STORAGE FOR NEW VIDEO SURVEILLANCE CAMERAS.
- ⑤ EACH CAMERA TO BE PROVIDED WITH 60 DAYS OF ON BOARD STORAGE. EACH CAMERA TO BE PROVIDED WITH A 5-YEAR LICENSE. CONTRACTOR TO COORDINATE WITH MANUFACTURER FOR START OF LICENSE TO START AT MATERIAL COMPLETION, NOT DATE OF PURCHASE.
- ⑥ ALL CAMERA SETTINGS & VIEWS TO BE PROGRAMMED & CONFIGURED BY CONTRACTOR TO OWNER'S SATISFACTION.
- ⑦ CONTRACTOR TO PROVIDE AND INSTALL ALL CATEGORY 6 PATCH CABLES.
- ⑧ CONTRACTOR TO COORDINATE WITH TELECOM CONTRACTOR FOR UTILIZATION OF DATA INFRASTRUCTURE TO ESTABLISH CONNECTION TO THE SECURITY NETWORK VLAN.
- ⑨ CONTRACTOR TO PROVIDE AND INSTALL POWER-OVER-ETHERNET SWITCH MOUNTED IN TELECOM RACK FOR VIDEO SURVEILLANCE SYSTEM.
- ⑩ CONTRACTOR TO INSTALL DITEK, POE, RACK MOUNTED SURGE PROTECTORS FOR ALL OUTDOOR CAMERAS TYPICAL TO DITEK DTK-RM12POE.
- ⑪ ALL EXTERIOR CAMERAS TO BE PROVIDED WITH TVSS DEVICES ON POWER & VIDEO SIGNAL ON CAMERA END TYPICAL TO DITEK MRIPOE DEVICES.



CAMERA SCHEDULE						
CAMERA #	CAMERA MODEL	CAMERA TYPE	LENS TYPE	MOUNTING REQUIREMENTS	FIELD OF VIEW	REFERENCE SHEET
C-1.01	DOME-W-5MP-60	5MP	3.6-10MM	INTERIOR CEILING MOUNTED	ENTRY VESTIBULE	LV-501
C-1.02	360-W-60	12MP	FISHEYE	INTERIOR CEILING MOUNTED	WAITING/FRONT DESK	LV-501
C-1.03	9C-H5A-3MH-6	3X3MP	3.3-5.7MM	INTERIOR CEILING MOUNTED	CHECKOUT/CORRIDOR	LV-501
C-1.04	360-W-60	12MP	FISHEYE	INTERIOR CEILING MOUNTED	STAFF STATION/MEDS ROOM DOOR	LV-501
C-1.05	360-W-60	12MP	FISHEYE	INTERIOR CEILING MOUNTED	MEDS ROOM	LV-501
C-1.07	9C-H5A-3MH-6	3X3MP	3.3-5.7MM	INTERIOR CEILING MOUNTED	STAFF ENTRANCE/CORRIDOR	LV-501
C-S.01	9C-H5A-3MH-6	3X3MP	3.3-5.7MM	EXTERIOR CORNER MOUNTED	EXTERIOR	LV-501
C-S.02	9C-H5A-3MH-6	3X3MP	3.3-5.7MM	EXTERIOR WALL MOUNTED	EXTERIOR	LV-501
C-S.03	12C-H5A-4MH-60	4X3MP	3.3-5.7MM	EXTERIOR CANOPY MOUNTED	VESTIBULE ENTRY/EXTERIOR	LV-501
C-S.04	9C-H5A-3MH-6	3X3MP	3.3-5.7MM	EXTERIOR CORNER MOUNTED	EXTERIOR	LV-501
C-S.05	12C-H5A-4MH-60	4X3MP	3.3-5.7MM	EMERGENCY CALL STATION MOUNTED	STAFF PARKING/EXTERIOR	LV-501

1 ONE-LINE DIAGRAM - VIDEO SURVEILLANCE SYSTEM

N.T.S.

P

N

M

L

K

J

H

G

F

E

D

C


B

A

12/17/2025 2:48:27 PM

PROJECT NO:	25132.00
DD/PKG:	12/18/2025

NOT ISSUED FOR
CONSTRUCTION








SHEET TITLE

DETAILS -
CAMERAS

SHEET NUMBER

LV-501

1 INTERIOR LAY-IN TILE CEILING
NOT TO SCALE2 INTERIOR GYP BOARD CEILING
NOT TO SCALE3 INTERIOR HARD CEILING
NOT TO SCALE4 INTERIOR LAY-IN TILE CEILING
NOT TO SCALE5 INTERIOR GYPSUM BOARD CEILING
NOT TO SCALE

P

N

M

L

K

J

H

G

F

E








D

C

B

A

12/17/2025 2:29 PM

1 DOUBLE DOOR DETAIL
NOT TO SCALE2 DOUBLE DOOR DETAIL
NOT TO SCALE3 DOUBLE DOOR DETAIL
NOT TO SCALE4 SINGLE DOOR DETAIL
NOT TO SCALE5 SINGLE DOOR DETAIL
NOT TO SCALE6 SINGLE DOOR DETAIL
NOT TO SCALE7 SINGLE DOOR DETAIL
NOT TO SCALE

P

N

M

L

K

J

H

G

F

E

D



C

B

A

12/17/2025 2:29 PM

PROJECT NO:	25132.00
DD PACKAGE	12/18/2025

F RATINGS - 2, 3 AND 4 HR (SEE ITEM 5)
T RATINGS - 0, 1/2 AND 2-3/4 HR (SEE ITEM 5)

KEY NOTES: (APPLY TO THIS DETAIL ONLY)

① FLOOR/WALL ASSEMBLY - MIN 2-1/2 IN. (64 MM) OR 4-1/2 IN. (114 MM) THICK REINFORCED CONCRETE. FLOOR MAY BE CONSTRUCTED OF ANY UL CLASSIFIED CONCRETE BLOCKS. FLOOR MAY ALSO BE CONSTRUCTED OF ANY UL CLASSIFIED HOLLOW-CORE PRECAST CONCRETE UNITS*. MAX DIAM. OF OPENING IS 6 IN. (152 MM). SEE CONCRETE BLOCKS (CAZ) AND PRECAST CONCRETE UNITS (CTV) CATEGORIES IN THE FIRE RESISTANCE DIRECTORY FOR NAMES OF MANUFACTURERS.

② SLEEVE - (OPTIONAL) - NOM 6 IN. (152 MM) DIAM (OR SMALLER) SCHEDULE 10 (OR HEAVIER) STEEL PIPE SLEEVE; NOM 6 IN. (152 MM) DIAM (OR SMALLER) NO. 26 GA (0.023 IN. OR 0.56 MM THICK) SHEET STEEL SLEEVE WITH SQUARE ANCHOR FLANGE SPOT WELDED TO SLEEVE AT APPROX MID-HEIGHT OR NOM 5 IN. (125 MM) DIAM (OR SMALLER) SCHEDULE 40 POLYVINYL CHLORIDE (PVC) PIPE SLEEVE CAST OR GROUTED INTO FLOOR OR WALL FLUSH WITH FLOOR OR WALL SURFACES. STEEL PIPE SLEEVE MAY BE INSTALLED TO PROJECT A MAX OF 2 IN. (51 MM) BEYOND THE FLOOR OR WALL SURFACES.

③ CABLES - AGGREGATE CROSS-SECTIONAL AREA OF CABLES IN SLEEVE TO BE MAX 45 PERCENT OF THE CROSS-SECTIONAL AREA OF THE SLEEVE. SEE ITEM 5 FOR SPECIFIC CABLE FILL REQUIREMENTS. TIGHT BUNDLE OF CABLES TO BE INSTALLED IN THE STEEL SLEEVE. THE ANNULAR SPACE WITHIN THE FIRESTOP SYSTEM SHALL BE A MIN OF 0 IN. (POINT CONTACT) TO A MAX OF 2 IN. IN 4 HR FIRE RATED ASSEMBLIES, THE ANNULAR SPACE BETWEEN THE FIRESTOP SYSTEM SHALL BE A MIN OF 1/4 IN. (6 MM) TO A MAX OF 1 IN. (25 MM). CABLES TO BE RIGIDLY SUPPORTED ON BOTH SIDES OF THE FLOOR OR WALL ASSEMBLY. ANY COMBINATION OF THE FOLLOWING TYPES AND SIZES OF CABLES MAY BE USED:

- A. MAX 400 PAIR NO. 24 AWG (OR SMALLER) COPPER CONDUCTOR CABLE WITH POLYVINYL CHLORIDE (PVC) JACKETING AND INSULATION.
- B. MAX 3/C NO. 2/0 AWG (OR SMALLER) ALUMINUM OR COPPER CONDUCTOR SERVICE ENTRANCE CABLE WITH PVC INSULATION AND JACKET.
- C. MAX 3/C NO. 2/0 AWG (OR SMALLER) COPPER CONDUCTOR PVC JACKETED ALUMINUM CLAD OR STEEL CLAD TECK 90 CABLE.
- D. MAX 3/C NO. 8 AWG (OR SMALLER) NONMETALLIC SHEATHED (ROMEX) CABLE WITH COPPER CONDUCTORS, INSULATION AND JACKET.
- E. MAX 1/C 1000 KCMIL (OR SMALLER) COPPER CONDUCTOR POWER CABLE WITH XLPE OR PVC INSULATION AND XLPE OR PVC JACKET.
- F. MAX RG59/U (OR SMALLER) COAXIAL CABLE WITH FLUORINATED ETHYLENE INSULATION AND JACKETING.
- G. MAX 62.5/48 FIBER OPTIC CABLE WITH PVC INSULATION AND JACKETING.
- H. MAX 4 PAIR NO. 24 AWG (OR SMALLER) COPPER CONDUCTOR DATA CABLE WITH PVC INSULATION AND JACKET.

④ THROUGH PENETRATING PRODUCT* - (NOT SHOWN) - MAX 4/C NO. 2/0 AWG (OR SMALLER) STEEL OR ALUMINUM ARMORED CABLE* OR METAL CLAD CABLE* WITH COPPER OR ALUMINUM CONDUCTORS. DIAM. OF CABLE BUNDLE (ITEM 3) INCLUDING ARMORED CABLE NOT TO EXCEED 4 IN. THROUGH PENETRATING PRODUCT TO BE RIGIDLY SUPPORTED ON BOTH SIDES OF A FLOOR OR WALL ASSEMBLY.



⑤ AFC CABLE SYSTEMS INC - PACKING MATERIAL 1-1/2, 2, 3 OR 4 IN. (51, 76 OR 102 MM) THICKNESS OF MIN 4 PCF (64 KG/M³) DENSITY OF SPHERICAL WOOL BATT INSULATION EIGHTLY PACKED INTO OPENING AS A PERMANENT FORM FOR 1, 2 OR 4 HR FIRE RATED ASSEMBLIES, RESPECTIVELY. PACKING MATERIAL TO BE RECESSED FROM TOP EDGE OF SLEEVE OR FROM TOP SURFACE OF CONCRETE IN CAST CONCRETE FLOOR ASSEMBLIES TO ACCOMMODATE THE REQUIRED THICKNESS OF FILL MATERIAL. PACKING MATERIAL TO BE RECESSED FROM BOTH EDGES OF SLEEVE OR FROM BOTH SURFACES OF ASSEMBLY IN WALLS AND IN FLOOR CONSTRUCTED WITH HOLLOW-CORE PRECAST CONCRETE UNITS TO ACCOMMODATE THE REQUIRED THICKNESS OF FILL MATERIAL.

⑥ FILL, VOID OR CAVITY MATERIAL* - SEALANT OR PUTTY - MIN 1/2 IN. (13 MM) THICKNESS OF FILL MATERIAL APPLIED WITHIN THE ANNULUS FOR 2 AND 3 HR F RATINGS. MIN 3/4 IN. (19 MM) THICKNESS OF FILL MATERIAL APPLIED WITH THE ANNULUS FOR 4 HR F RATING. IN FLOORS, FILL MATERIAL TO BE INSTALLED FLUSH WITH TOP EDGE OF SLEEVE OR TOP SURFACE OF FLOOR. IN WALLS AND IN FLOOR CONSTRUCTED OF HOLLOW-CORE PRECAST CONCRETE UNITS, FILL MATERIAL TO BE INSTALLED FLUSH WITH BOTH ENDS OF SLEEVE OR BOTH SURFACES OF ASSEMBLY. F AND T RATINGS OF FIRESTOP SYSTEM ARE DEPENDENT UPON THE THROUGH OPENING SIZE, THICKNESS OF CONCRETE, SLEEVE TYPE AND PERCENT CABLE FILL, AS SHOWN IN THE FOLLOWING TABLE:

MAX OPENING DIAM	MIN CONCRETE THICKNESS	OPTIONAL SLEEVE TYPE	CABLE TYPE	PERCENT CABLE FILL	F RATING	T RATING
6 IN. (152 MM)	2-1/2 IN. (64 MM)	PVC	A TO H, 3A	37	2 HR	0 HR
6 IN. (152 MM)	2-1/2 IN. (64 MM)	PVC	H	45	2 HR	0 HR
6 IN. (152 MM)	2-1/2 IN. (64 MM)	STEEL	A TO H, 3A	37	2 HR	0 HR
6 IN. (152 MM)	2-1/2 IN. (64 MM)	STEEL	H	45	2 HR	0 HR
6 IN. (152 MM)	4-1/2 IN. (114 MM)	STEEL	A TO H, 3A	34	3 HR	1/2 HR
6 IN. (152 MM)	4-1/2 IN. (114 MM)	STEEL	H	45	3 HR	1/2 HR
2 IN. (51 MM)	4-1/2 IN. (114 MM)	STEEL	H	40	3 HR	2-3/4 HR
2 IN. (51 MM)	4-1/2 IN. (114 MM)	STEEL	H	40	4 HR	2-3/4 HR

SPECIFIED TECHNOLOGIES INC - SPECSEAL SERIES SSS SEALANT OR SPECSEAL LCI SEALANT. WHEN MIN FLOOR OR WALL THICKNESS IS 4-1/2 IN. (114 MM), SPECSEAL PUTTY MAY BE USED.
*BEARING THE UL CLASSIFICATION MARK

1 FIRESTOP SYSTEM - C-AJ-3154
NOT TO SCALE

F RATINGS -1 AND 2 HR (SEE ITEM 1)
T RATING - 3/4 HRANSI/UL1479 (ASTM E814)
F RATINGS -1, 2 AND 3 HR (SEE ITEM 1)
T RATINGS -1, 1-1/2 AND 2 HR (SEE ITEM 1)
L RATING AT AMBIENT - LESS THAN 1 TO 2.3 CFM/DEVICE MODULE (SEE ITEM 2)
L RATING AT 400 F - LESS THAN 1 TO 2.3 CFM/DEVICE MODULE (SEE ITEM 2)

KEY NOTES: (APPLY TO THIS DETAIL ONLY)

① WALL ASSEMBLY - THE 1 OR 2 HR FIRE RATED GYPSUM BOARD/STUD WALL ASSEMBLY SHALL BE CONSTRUCTED OF THE MATERIALS AND IN THE MANNER SPECIFIED IN THE INDIVIDUAL U300, U400 OR V400 SERIES WALL AND PARTITION DESIGNS IN THE UL FIRE RESISTANCE DIRECTORY AND SHALL INCLUDE THE FOLLOWING CONSTRUCTION FEATURES:

A. STUDS - WALL FRAMING MAY CONSIST OF EITHER WOOD STUDS OR STEEL CHANNEL STUDS. WOOD STUDS TO CONSIST OF NOM. 2 X 4 IN. (51 X 102MM) LUMBER SPACED 16 IN. (406MM) OC. STEEL STUDS TO BE MIN 3-1/2 IN. (76MM) WIDE AND SPACED MAX 14 IN. (610MM) OC.

B. GYPSUM BOARD - THICKNESS, NUMBER OF LAYERS, FASTENER TYPE AND SHEET ORIENTATION SHALL BE AS SPECIFIED IN THE INDIVIDUAL U300, U400 OR V400 SERIES DESIGN IN THE UL FIRE RESISTANCE DIRECTORY. MAX DIAM. OF OPENING IS 4-1/2 IN. (114 MM).

THE HOURLY F RATING OF THE FIRESTOP SYSTEM IS EQUAL TO THE HOURLY FIRE RATING OF THE WALL ASSEMBLY IN WHICH IT IS INSTALLED.

② STEEL SLEEVE - NOM. 4 IN. (102MM) DIAM. (OR SMALLER) STEEL ELECTRICAL METALLIC TUBING (EMT), STEEL CONDUIT OR SCHEDULE 5 (OR HEAVIER) STEEL PIPE SLEEVE FRICTION-FITTED INTO WALL ASSEMBLY. SLEEVE MAY BE INSTALLED FLUSH WITH OR EXTEND UP TO 18 IN. (46 CM) BEYOND ONE OR BOTH WALL SURFACES.

③ CABLES - AGGREGATE CROSS-SECTIONAL AREA OF CABLES IN STEEL SLEEVE TO BE MAX. 48 PERCENT OF THE AGGREGATE CROSS-SECTIONAL AREA OF THE SLEEVE. CABLES TO BE BUNDLED AND RIGIDLY SUPPORTED ON BOTH SIDES OF WALL ASSEMBLY. THE ANNULAR SPACE BETWEEN THE CABLES AND THE SLEEVE SHALL BE MIN. 0 IN. (POINT CONTACT) TO MAX. 1-1/2 IN. (38MM). ANY COMBINATION OF THE FOLLOWING TYPES AND SIZES OF COPPER CONDUCTOR CABLE MAY BE USED:

- A. MAX 200 PAIR NO. AWG (OR SMALLER) COPPER CONDUCTOR CABLE WITH POLYVINYL CHLORIDE (PVC) JACKETING AND INSULATION.
- B. MAX 3/C NO. 2/0 AWG (OR SMALLER) ALUMINUM OR COPPER CONDUCTOR SERVICE ENTRANCE CABLE WITH PVC INSULATION AND JACKET.
- C. MAX 3/C NO. 8 AWG (OR SMALLER) NONMETALLIC SHEATHED (ROMEX) CABLE WITH COPPER CONDUCTORS, PVC INSULATION AND JACKET.
- D. MAX 7/C NO. 2/0 AWG (OR SMALLER) MULTICONDUCTOR POWER AND CONTROL CABLES WITH XLPE OR PVC INSULATION AND XLPE OR PVC JACKET.
- E. MAX RG59/U (OR SMALLER) COAXIAL CABLE WITH FLUORINATED ETHYLENE INSULATION AND JACKETING.
- F. MAX 62.5/48 FIBER OPTIC CABLE WITH PVC INSULATION AND JACKETING.
- G. MAX 4 PAIR NO. 24 AWG (OR SMALLER) COPPER CONDUCTOR DATA CABLE WITH PVC INSULATION AND JACKET.
- H. MAX 4/C NO 2/0 ALUMINUM OR COPPER CONDUCTOR ALUMINUM OR STEEL METAL-CLAD# OR ARMORED-CLAD# CABLE.

④ FIRESTOP SYSTEM - THE FIRESTOP SYSTEM SHALL CONSIST OF THE FOLLOWING:

A. PACKING MATERIAL - WHEN REQUIRED (SEE TABLE IN ITEM 3B), MIN. 1 IN. (25MM) THICKNESS OF MIN. 4.0 PCF (64 KG/M³) MINERAL WOOL BATT INSULATION FIRMLY PACKED INTO EACH END OF SLEEVE AS A PERMANENT FORM. PACKING MATERIAL TO BE RECESSED FROM EACH END OF SLEEVE AS REQUIRED TO ACCOMMODATE THE REQUIRED THICKNESS OF FILL MATERIAL.

B. FILL, VOID OR CAVITY MATERIAL* - SEALANT OR PUTTY - FILL MATERIAL APPLIED TO APPROPRIATE THICKNESS WITHIN STEEL SLEEVE, FLUSH WITH EDGES OF STEEL SLEEVE ON BOTH SURFACES OF WALL. MIN. 1/2 IN. (13MM) DIAM. BEAD OF SEALANT OR 'ROPE' OF PUTTY SHALL BE APPLIED AROUND THE PERIMETER OF THE SLEEVE ON EACH SIDE OF THE WALL WHEN SLEEVE EXTENDS BEYOND SURFACE OF WALL. SEE TABLE BELOW FOR FILL MATERIAL THICKNESS REQUIREMENTS.

SEALANT OR PUTTY TYPE	THICKNESS	PACKING MATERIAL REQUIRED
SPECSEAL SERIES SSS SEALANT OR LCI SEALANT	1/2 IN. (13 MM)	YES
SPECSEAL SERIES SSS SEALANT OR LCI SEALANT	1 IN. (25 MM)	NO
SPECSEAL PUTTY	1 IN. (25 MM)	NO

SPECIFIED TECHNOLOGIES INC - SPECSEAL SERIES SSS SEALANT OR SPECSEAL LCI SEALANT. WHEN MIN FLOOR OR WALL THICKNESS IS 4-1/2 IN. (114 MM), SPECSEAL PUTTY MAY BE USED.
*BEARING THE UL CLASSIFICATION MARK

2 FIRESTOP SYSTEM - W-L-3210
NOT TO SCALE

2A. FIRESTOP DEVICE - EXTENSION MODULE - (OPTIONAL, NOT SHOWN) - MODULE ATTACHED TO ENDS OF FIRESTOP DEVICE (ITEM 2) TO INCREASE ITS LENGTH TO FACILITATE INSTALLATION IN THICK WALLS. EACH MODULE CONSISTS OF A 4-1/2 BY 18 BY 18 BY 152 MM LONG CALV STEEL TUBE WITH AN INTUMESCENT MATERIAL LINING. EXTENSION MODULE TO BE INSTALLED IN ACCORDANCE WITH THE ACCOMPANYING INSTALLATION INSTRUCTIONS. WHEN MODULE IS USED, FIRESTOP DEVICE (ITEM 2) AND EXTENSION MODULE SECURED IN PLACE BY MEANS OF STEEL PLATES INSTALLED WITH GASKETING MATERIAL SUPPLIED WITH PRODUCT. STEEL PLATES INSTALLED ON BOTH SIDES OF WALL AND SECURED TO EACH DEVICE OR EXTENSION MODULE BY MEANS OF STEEL SET SCREWS PROVIDED WITH PLATES. FIRESTOP DEVICE AND EXTENSION MODULE ASSEMBLY TO BE INSTALLED WITH ENDS PROJECTIONS AN EQUAL DISTANCE BEYOND EACH SURFACE OF THE WALL ASSEMBLY.

SPECIFIED TECHNOLOGIES INC - EZ PATH SERIES 44+ EXTENSION

③ CABLES - CABLES MAY REPRESENT A 0 TO MAX 100 PERCENT VISUAL FILL WITHIN THE LOADING AREA FOR EACH FIRESTOP DEVICE MODULE. CABLES TO BE RIGIDLY SUPPORTED ON BOTH SIDES OF THE WALL ASSEMBLY. ANY COMBINATION OF THE FOLLOWING TYPES OF CABLES MAY BE USED:

- A. MAX 400 PAIR NO. 24 AWG (OR SMALLER) COPPER CONDUCTOR TELECOMMUNICATION CABLE WITH POLYVINYL CHLORIDE (PVC) OR PLENUM-RATED JACKETING & INSULATION.
- B. MAX 750 KCMIL SINGLE COPPER CONDUCTOR POWER CABLE WITH XLPE JACKET AND INSULATION.
- C. MAX 7/C NO. 2/0 AWG COPPER CONDUCTOR CONTROL CABLE WITH PVC OR XLPE JACKET AND INSULATION.
- D. MAX 3/C NO. 2/0 AWG METAL CLAD OR ARMORED CABLE WITH STEEL OR ALUMINUM JACKET.
- E. MAX 3/C NO. 8 AWG MM CABLE (ROMEX) WITH PVC INSULATION AND JACKETING.
- F. MAX FOUR PAIR NO. 24 AWG (OR SMALLER) COPPER CONDUCTOR DATA CABLE WITH PVC OR PLENUM RATED JACKETING & INSULATION.
- G. COAXIAL CABLE WITH FLUORINATED ETHYLENE OR PVC INSULATION AND JACKETING HAVING A MAX DIAM OF 5/8 IN. (16 MM).
- H. OPTICAL FIBER CABLE WITH PVC OR POLYETHYLENE (PE) JACKET AND INSULATION AND HAVING A MAX DIAM OF 5/8 IN. (16 MM).
- I. MAX RG59/U COAXIAL CABLE WITH FLUORINATED ETHYLENE, POLYETHYLENE (PE), PVC OR PLENUM RATED JACKETING & INSULATION.




FOR THE SERIES 44+ FIRESTOP DEVICE AND WHEN ITEM 3A, 3B, 3C, 3D, 3E OR 3I IS USED, THE T, FT AND FTH RATINGS ARE 1 HR. WHEN ITEM 3F OR 3G IS USED, THE T, FT AND FTH RATINGS ARE 1 AND 1-1/2 HR FOR 1 AND 2 HR RATED ASSEMBLIES RESPECTIVELY. WHEN ITEM 3H IS USED, THE T, FT AND FTH RATINGS ARE 1 AND 2 HR FOR 1 AND 2 HR RATED ASSEMBLIES RESPECTIVELY. WHEN DEVICE IS EMPTY, THE T, FT AND FTH RATINGS ARE 1 AND 1-1/2 HR FOR 1 AND 2 HR RATED ASSEMBLIES RESPECTIVELY. WHEN TWO BANKS OF FIRESTOP DEVICE MODULES ARE INSTALLED, THE T, FT AND FTH RATINGS ARE 1 HR.

④ FILL, VOID OR CAVITY MATERIAL* - SEALANT OR PUTTY - (NOT SHOWN) - AS AN ALTERNATE TO GYPSUM JOINT COMPOUND, THE GAP BETWEEN THE FIRESTOP DEVICE MODULE AND THE CUTOUT IN THE GYPSUM BOARD MAY BE FILLED WITH FILL MATERIAL ON EACH SIDE OF THE WALL ASSEMBLY WHEN MULTI-GANG STEEL WALL BRACKETS ARE INSTALLED DIRECTLY AGAINST THE WOOD OR STEEL STUDS.

SPECIFIED TECHNOLOGIES INC - SPECSEAL SERIES SSS SEALANT, SPECSEAL LCI SEALANT, SPECSEAL PUTTY

*BEARING THE UL LISTING MARK

* INDICATES SUCH PRODUCTS SHALL BEAR THE UL OR CUL CERTIFICATION MARK FOR

P
N
M
L
K
J
H
G
F
E
D
C
B
A12/17/2025 2:48:29 PM
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19

GENERAL NOTES:

A. TELECOMMUNICATIONS BONDING BACKBONE (TBB) SHALL BE A CONTINUOUS CONDUCTOR AND SHALL BE SPICED TO TELECOMMUNICATIONS GROUND BUSBARS WITH A SHORT BONDING CONDUCTOR. USE CONDUCTOR TABLE TO CALCULATE TBB SIZE. CONTRACTOR TO COMPLY WITH ALL REQUIREMENTS OF ANSI/TIA-607C.

B. GROUNDING EQUALIZER (GE) SHALL BE A CONTINUOUS CONDUCTOR AND SHALL BE SPICED TO TELECOMMUNICATIONS GROUND BUSBARS WITH A SHORT BONDING CONDUCTOR. USE CONDUCTOR TABLE TO CALCULATE GE SIZE. CONTRACTOR TO COMPLY WITH ALL REQUIREMENTS OF ANSI/TIA-607C.

C. ALL GROUNDING LUGS SHALL BE TWO HOLE, NO EXCEPTIONS.

CONDUCTOR TABLE	
LINEAR LENGTH (FT.)	SIZE (AWG)
LESS THAN 13	6
14 - 17	4
21 - 26	3
27 - 33	2
34 - 41	1
42 - 52	1/0
53 - 66	2/0
GREATER THAN 67	3/0

KEY NOTES:

① TELECOM CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS MAIN GROUNDING BUSBAR (TMGB). TMGB SHALL BE PRE-DRILLED COPPER BUSBAR WITH STANDARD NEMA BOLT HOLE SIZING AND SPACING. MINIMUM SIZING SHALL BE $\frac{1}{4}$ " THICK X 4" WIDE X 24' LENGTH.

② TELECOM CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS GROUNDING BUSBAR (TGB). TGB SHALL BE PRE-DRILLED COPPER BUSBAR WITH STANDARD NEMA BOLT HOLE SIZING AND SPACING. MINIMUM SIZING SHALL BE $\frac{1}{4}$ " THICK X 4" WIDE X 18' LENGTH.

③ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL BONDING CONDUCTOR FOR TELECOMMUNICATIONS (TBC) TO BUILDING MAIN ELECTRICAL GROUNDING SYSTEM. USE CONDUCTOR TABLE TO CALCULATE RCT SIZE. NOTE: THE RCT AND THE TBB SHALL BE THE SAME SIZE BASED UPON THE LARGER CONDUCTOR.

④ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL BONDING CONDUCTOR FOR TELECOMMUNICATIONS (TBC) TO ELECTRICAL PANELS WITHIN THE MDF AND IDF ROOMS. USE CONDUCTOR TABLE TO CALCULATE BCT SIZE.

⑤ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL BONDING CONDUCTOR TO THE BUILDING STEEL. USE CONDUCTOR TABLE TO CALCULATE CONDUCTOR SIZE. SAME SIZE AS (TBB).

⑥ TELECOMMUNICATIONS CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS GROUNDING BUSBAR [TEBC] ROUTED ON LADDER BACK TO BOND EACH TELECOMMUNICATIONS RACK OR CABINET TO THE TMGB OR TGB. USE CONDUCTOR TABLE TO CALCULATE CONDUCTOR SIZE. EACH TEBC SHALL BE A CONTINUOUS CONDUCTOR. SPLICING A #6 AWG CONDUCTOR USING AN IRREVERSIBLE CRIMP CONNECTOR OR EXOTHERMIC WELD TO THE TEBC IN EACH RACK OR CABINET MOUNTED GROUNDING BUSBAR DAISY CHAINING FROM ONE RACK OR CABINET TO ANOTHER IS NOT ACCEPTABLE.

⑦ TELECOMMUNICATIONS CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS EQUIPMENT BONDING CONDUCTOR (TEBC) FROM TMGB OR TGB TO EACH LEVEL OF THE LADDER RACK SYSTEM WITH A #6 AWG CONDUCTOR. EACH SECTION OF THE LADDER RACK SYSTEM SHALL BE BONDED TOGETHER WITH CABLE RUNWAY STRAPS.

⑧ TELECOMMUNICATIONS CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS EQUIPMENT BONDING CONDUCTOR (TEBC) FROM TMGB OR TGB TO EACH EMT CONDUIT USED FOR BACKBONE CABLEING WITH A #6 AWG CONDUCTOR. CONDUIT SHALL BE BONDED ON BOTH ENDS.


⑨ TELECOMMUNICATIONS CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS EQUIPMENT BONDING CONDUCTOR (TEBC) FROM TMGB OR TGB TO EACH METAL JACKET OF THE ARMORED FIBER OPTIC CABLE WITH A #6 AWG CONDUCTOR. METAL JACKET SHALL BE BONDED ON BOTH ENDS.


⑩ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS EQUIPMENT BONDING CONDUCTOR (TEBC) FROM TMGB OR TGB TO SUB FLOOR PEDESTAL SUPPORT SYSTEM USED FOR DISTRIBUTING HORIZONTAL CABLEING UNDER THE FLOOR. USE CONDUCTOR TABLE TO CALCULATE CONDUCTOR SIZE.

⑪ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL GROUNDING EQUALIZER (GE) CONDUCTOR. THE GE CONNECTS THE TELECOMMUNICATIONS GROUNDING BUSBARS IN THE SAME-FLOOR TELECOMMUNICATION ROOMS SERVED FROM DIFFERENT TBB CONDUCTORS. USE CONDUCTOR TABLE TO CALCULATE GE CONDUCTOR SIZE.


⑫ IRREVERSIBLE COMPRESSION TYPE CONNECTOR OR EXOTHERMIC WELD.

⑬ ELECTRICAL CONTRACTOR TO PROVIDE AND INSTALL TELECOMMUNICATIONS BONDING BACKBONE CONDUCTOR (TBB) ROUTED IN CONDUIT TO BOND EACH TELECOMMUNICATIONS ROOM TO THE TMGB. USE CONDUCTOR TABLE TO CALCULATE CONDUCTOR SIZE. THE TBB SHALL BE A CONTINUOUS CONDUCTOR.


1 GROUNDING
NOT TO SCALE




1 TYPICAL 2-PORT OUTLET
NOT TO SCALE




2 TYPICAL 1-PORT OUTLET
NOT TO SCALE




3 TYPICAL DISPLAY OUTLET
NOT TO SCALE




4 VIDEO SURVEILLANCE CAMERA
TYPICAL ETHERNET BISCUIT
NOT TO SCALE




5 WIRELESS ACCESS POINT
TYPICAL ETHERNET BISCUIT
NOT TO SCALE




6 RJ45 JACK TERMINATION
NOT TO SCALE




7 WALL MOUNT CABLE TRAY INSTALLATION
NOT TO SCALE




8 SUSPENDED BISCUIT JACK
NOT TO SCALE



9 CEILING MOUNT CABLE TRAY INSTALLATION
NOT TO SCALE



10 ACCESSIBLE CEILING CABLE
INSTALLATION DETAIL
NOT TO SCALE



11 TYPICAL DATA OUTLET
INSTALLATION REQUIREMENTS
NOT TO SCALE

GENERAL NOTES:

- A. ALL DATA OUTLETS TO BE COORDINATED WITH ELECTRICAL POWER LOCATIONS. DATA OUTLETS SHALL BE MOUNTED ADJACENT TO POWER RECEPTACLES AT SAME HEIGHT.
- B. DATA OUTLET SHALL EITHER BE MOUNTED ON OPPOSITE SIDE OF SHARED STUD AS POWER OR DATA SHALL BE MOUNTED ON ADJACENT STUD TO POWER IN SAME WALL CAVITY.
- C. TYPICAL DATA OUTLET HEIGHT SHALL BE 18", UNLESS OTHERWISE NOTED. COORDINATE EXACT MOUNTING HEIGHTS AND ORIENTATION WITH ELECTRICAL AND ARCHITECTURAL PLAN.
- D. CONTRACTOR TO VERIFY ALL DATA OUTLETS TO BE PROVIDED WITH ADJACENT POWER RECEPTACLE. SUBMIT RFI IF CONDITION DOES NOT EXIST.

PROJECT NO:	25132.00
DD PACKAGE	12/18/2025

P
N
M
L
K
J
H
G
F
E
D
C
B
A