

**SECTION 102123
CUBICLE CURTAINS AND TRACK**

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Surface mounted overhead curtain track and guides.
- B. Cubicle curtains.

1.02 SUBMITTALS

- A. See Section 013000 - Administrative Requirements, for submittal procedures.
- B. Shop Drawings: Indicate a reflected ceiling plan view of curtain track, hangers and suspension points, attachment details, schedule of curtain sizes.
- C. Samples: Submit 12 by 12 inch (300 by 300 mm) sample patch of curtain cloth with representative top, bottom, and edge hem stitch detail, heading with reinforcement and carrier attachment to curtain header.
- D. Maintenance Data: Include recommended cleaning methods and materials and stain removal methods.

1.03 DELIVERY, STORAGE, AND HANDLING

- A. Accept curtain materials on site and inspect for damage.
- B. Store curtain materials on site and deliver to Owner for installation when requested.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Cubicle Track and Curtains:
 - 1. A. R. Nelson Co: www.arnelson.com/#sle.
 - 2. Construction Specialties, Inc: www.c-sgroup.com/#sle.
 - 3. Imperial Fastener Co., Inc: www.imperialfastener.com/#sle.
 - 4. Inpro: www.inprocorp.com/#sle.
 - 5. Krieger Textiles; Cubicle Fabrics: www.kriegertextiles.com/#sle.

2.02 TRACKS AND TRACK COMPONENTS

- A. Tracks: Extruded aluminum sections; one piece per track run.
 - 1. Profile: Channel.
 - 2. Mounting: Surface.
 - 3. Track End Stop: To fit track section.
 - 4. Finish on Exposed Surfaces: White enamel.
- B. Curtain Carriers: Nylon rollers, size and type compatible with track; designed to eliminate bind when curtain is pulled; fitted to curtain to prevent accidental curtain removal.
- C. Installation Accessories: Types required for specified mounting method and substrate conditions.

2.03 CURTAINS

- A. See drawings for type and manufacturer
- B. Cubicle Curtains:
 - 1. Material: Close weave polyester; anti-bacterial, self deodorizing, sanitized, and preshrunk.
 - 2. Open Mesh Cloth: Open weave to permit air circulation; flameproof material, manufacturer's standard color.
- C. Curtain Fabrication:
 - 1. Width of curtain to be 10 percent wider than track length.

2. Include open mesh cloth at top 20 inches (508 mm) of curtain for room air circulation, attached to curtain as specified above.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that surfaces and supports above ceiling are ready to receive work of this Section.
- B. Verify that field measurements are as indicated.

3.02 INSTALLATION

- A. Install curtain track to be secure, rigid, and true to ceiling line.
- B. Secure track to ceiling system.
- C. Install end cap and stop device.
- D. Install curtains on carriers ensuring smooth operation.

END OF SECTION